



EN ISO 20344:2011 

ATLANTIDA
STELVIO
80087-00L

S3 HRO HI SRC

Size: 38-48
Weight: 765 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Engineering, Farming and
Gardening



FEATURES

UPPER
Greased Nubuk Dakar Leather
Hydro
Full Grain Leather Hydro

LINING
3D Air circulation 320 gr.

ANTISLIP LINING
DUALMICRO

INSOLE
Blowfit

TOE CAP
CTC- Composite Toe Cap

RESISTANCE TO PERFORATION
Zero(K) Perforation resistant

TYPE
Ankle boot

SOLE
PU-RUBBER VIBRAM-HRO-SRC
Sole with anti-wear scaff cap.
Outsole in VIBRAM rubber,
resistant to 300° C by contact
(HRO), to acids and oils. Design
with self-cleaning outsole, with
SRC Antislip standard.



SRC (SRA+SRB)

		SOLE 80 PU - RUBBER
SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	0.43 0.35
SRB STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	0.19 0.13

EN ISO 20344:2011

TECHNOLOGIES

Removable Insole

BLOWFIT

The upper part in FLYFIT, directly in contact with the foot, means transpiration and comfort. Under the heel, a support in EVA keeps the shape and resistance over time, efficiently supporting the bodyweight.



Protection elements

ZERO(k)
ANTIPERFORATION

 Composite Toe Cap

Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



Lateral stability

dynamic control technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features

WED
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.