



EN ISO 20344:2011 

ENDURANCE  
**CORVARA**  
81087-06L

**S3 SRC**

**Size:** 36-48  
**Weight:** 715 gr.

**Fit:** 11

**Working Environment:**  
Building, Finishing-off building,  
Farming and Gardening,  
Multipurpose



**FEATURES**

**UPPER**  
Greased Nubuk Dakar Leather  
Hydro  
Full Grain Leather Hydro

**LINING**  
3D Air circulation 320 gr.

**ANTISLIP LINING**  
DUALMICRO

**INSOLE**  
Blowfit

**TOE CAP**  
CTC- Composite Toe Cap



**RESISTANCE TO PERFORATION**  
Zero(K) Perforation resistant

**TYPE**  
Ankle boot

**SOLE**  
**PU DUAL-DENSITY SRC**  
Two-component PU sole with anti-wear scaffold cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.



**SRC (SRA+SRB)**

				SOLE B1 PU - PU
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °°) ≥0.28	<b>0.52</b>	<b>0.48</b>	
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °°) ≥0.13	<b>0.23</b>	<b>0.18</b>	EN ISO 20344:2011

**TECHNOLOGIES**

**Removable Insole**

**BLOWFIT**

The upper part in FLYFIT, directly in contact with the foot, means transpiration and comfort. Under the heel, a support in EVA keeps the shape and resistance over time, efficiently supporting the bodyweight.



**Protection elements**

**ZERO(k)**  
ANTIPERFORATION

 Composite Toe Cap

Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



**Lateral stability**

**dynamicControl**  
technology

Ergonomic rigid structure. It accommodates the heel, adjusting the foot support and control of the ankle in sideways movements. The plastic material increases protection of the ankle against sharp or pointy objects.



**Torsional stability**

**STABIL•ACTIVE**


Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**

**WED**  
Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**

**DUALMICRO**  
DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.