



EN ISO 20345:2011



ENDURANCE
LABRADOR

81152-00L

S3 SRC

Size: 36-48
Weight: 740 gr.

Fit: 11

Working Environment:
Building, Wood-metal carpentry,
Farming and Gardening,
Multipurpose



FEATURES

UPPER

Greased Nubuk Leather Hydro
1,8-2,0 mm
Fabric of High Tenacity
Pu Coated Leather 1,8-2,0 mm

LINING

3D Air circulation 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

Climaction-Fit 337

TOE CAP

Fiber cap SXT

RESISTANCE TO PERFORATION

Textile resistant to 3.0 mm nail

TYPE

Ankle boot

SOLE

PU DUAL-DENSITY SRC

Two-component PU sole with anti-wear scaff cap and high-comfort in-between insole. Outsole with self-cleaning tread pattern, with a formula designed to ensure greater grip. SRC Antislip standard.



SRC (SRA+SRB)



SOLE 81
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.52
	HEEL (CONTACT ANGLE °) ≥ 0.28	
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.23
	HEEL (CONTACT ANGLE °) ≥ 0.13	

EN ISO 20345:2011

TECHNOLOGIES


Removable Insole

climaction fit

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



Protection elements



Composite toecap with fiberglass. Resistant to over 200J. Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable



Lateral stability

dynamic HC control technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features



Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



Other

DUALMICRO DUALMICRO

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.