



EN ISO 20345:2011 

**POLAR**  
**STELVIO**  
**88087-17L**

**S3 HRO HI WR SRC**

**Size:** 38-48  
**Weight:** 865 gr.

**Fit:** 11


**Working Environment:**  
 Building, Farming and Gardening,  
 Mountains, Wood-metal  
 carpentry



**FEATURES**

- UPPER**  
Greased Nubuk Dakar Leather  
Hydro  
Reflex insert  
Full Grain leather Hydro
- LINING**  
3D Air circulation 320 gr.
- ANTISLIP LINING**  
DUALMICRO
- INSOLE**  
Blow-fit 2.0
- TOE CAP**  
CTC- Composite Toe Cap
- RESISTANCE TO PERFORATION**  
Zero(K) Perforation resistant
- TYPE**  
Ankle boot

**SOLE**  
**PU-RUBBER VIBRAM®-HRO-SRC**  
 Sole resistant to 300°C by contact.  
 With scaff cap and compound  
 designed with VIBRAM® for  
 stability and grip performance.  
 Outsole designed to strike the  
 ground better and to improve self-  
 cleaning. With anti-wear scaff cap.



**SRC (SRA+SRB)**

SOLE 88  
**PU - RUBBER**

<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32	<b>0.34</b>
	HEEL (CONTACT ANGLE °) ≥0.28	
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18	<b>0.19</b>
	HEEL (CONTACT ANGLE °) ≥0.13	

EN ISO 20345:2011

**TECHNOLOGIES**

**Removable Insole**  
**blow fit 2.0**

Anatomical and ergonomic removable insole with Flyfit, in direct contact with the foot, transpiring, and comfortable. The E.V.A. HD perforad and thermoformed support ensures comfort and energy absorption



**Protection elements**  
**ZERO(k)**  
 ANTIPERFORATION 

Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic. Athermic. Not detected by metal detector. Fabric anti-perforation foil. Resistant to over 1100 N with zero perforation.



**Lateral stability**  
**dynamic HC control technology**

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**  
**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**  
**WED**  
 Wire Electricity Discharge

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**  
**DUALMICRO DUALWICKO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.