



RawInut™ Flexi-Plug

● A problem solving fixing suitable for use in virtually any construction material, solid or hollow.



- 1. Resistant to vibration and corrosion.
- 2. Flange holds fixing flush to wall surface.
- 3. Sleeve compresses to provide secure fixing, even in irregular shaped holes.
- 4. Made from synthetic rubber for more severe conditions.
- 5. Bonded brass insert.

Typical Applications:


- Fixing to virtually any material, either solid or hollow, eg metal sheet, car panels, thin panel, plasterboard, plywood, glass, plastic, etc.
- Secure fixing in brittle or unknown substrates.
- Ideal for fixing in irregular or oversized holes.

Product Specification


DESC.	SCREW LENGTH (mm)	HOLE DIA. (mm)	FLANGE THICKNESS (mm)	LENGTH (mm)	GRIP RANGE (mm)	FIXINGS PER PACK		BOX PRODUCT CODE
						RETAIL	BOX	
*3240 M3	30	8	1.2	24.0	6-14	4	50	09-040
*4100 M4	20	8	1.4	12.6	0-4	4	50	09-100
*4240 M4	30	8	1.2	24.0	6-14	-	50	09-130
*5150 M5	20	10	0.9	14.1	0-5	-	50	09-195
*5250 M5	30	10	1.3	26.1	8-16	4	50	09-235
*5400 M5	50	10	1.3	39.8	20-30	-	50	09-317
6150 M6	-	13	1.3	16.0	0-3	-	50	09-355
6250 M6	-	13	2.0	26.7	6-26	-	50	09-385
6350 M6	-	13	1.3	35.0	11-23	-	50	09-415
8250 M8	-	16	5.0	27.9	4-10	-	50	09-473
8300 M8	-	18	1.2	30.0	6-15	-	50	09-475
8500 M8	-	18	2.0	50.0	15-39	-	50	09-533
1055 M10	-	20	1.3	55.0	20-36	-	25	09-594
1275 M12	-	24	1.3	80.0	30-50	-	20	09-654

*Also available without screws.


Installation




1. Drill appropriate diameter hole. For solid materials, drill hole to length of screw. Clean out hole and remove sharp edges to avoid damaging fixing.



2. Insert the fixing up to its flange.



3. Place fixture in position. Insert screw and tighten to compress sleeve and form a secure fixing. Do not overtighten.



4. Works equally well in uniform or irregularly shaped holes.