

TRAFFIC-LINE Impact Protection - White



Where discreet protection is required we have developed **TRAFFIC-LINE** Impact Protection in pure white colour. Manufactured in flexible and anti-aging Polyurethane (PU) foam with a non-porous skin **TRAFFIC-LINE** Impact protection is highly suitable for applications in hospitals, laboratories, food-processing industry, offices, clean rooms etc.

- Non-porous surfaces
- Temperature resistant from -40°C to +90°C
- Fire classification to UL94
- Indoor and Outdoor use

Finish:
Length: 1,000mm
Colour: White

- Indoor and Outdoor use
- White colour
- UV and solvent resistant
- Temperature resistant
- Silicone free
- Easily cut to size on site (sharp knife or fine saw blade)

Available in 7 profiles (5 standard and 2 external corner elements) – other profiles available on request).

TRAFFIC-LINE Impact Protection - Magnetic



An innovative development of our PU foam Impact Protection profiles, the magnetic strips are an integral part of the profile which are easily attached to steel surfaces. A simple solution for applications that do not require permanent protection or areas that require regular thorough cleaning. Manufactured in a high quality, age resistant, flexible Polyurethane (PU) foam.

- UV and solvent resistant
- Silicone free
- For Indoor use*
- Temperature resistant from -40°C to +90°C
- Fire resistant to UL94

- For Indoor use
- Yellow/black to DIN 4844
- UV and solvent resistant
- Temperature resistant
- Easily cut to size on site (sharp knife or fine saw blade)

***OPTION:** For outdoor use the ends are additionally sealed (Additional cost).

Finish:
Length: 1,000mm
Colour: Yellow/black

Most profiles can be supplied with magnetic strips.

White	Profile protection Semi-Circular 40/40/8	Edge protection Right-Angle 30/30	Edge protection Semi-Circular 40/40	Surface protection Semi-circular 40/32	Surface protection Rectangle 60/20	External tri-corners	External corners
Fixing:	push on		self adhesive				
Delivery weight (kg/ea.)	0.7	0.5	0.7	0.7	0.7	0.2	0.2
Reference	422.18.250	422.15.712	422.15.039	422.18.541	422.18.163	422.14.008	422.17.487
Typical despatch time (working days)	1 / 2 days						

Magnetic	Edge protection Trapeze 40/40	Edge protection Right-Angle 30/30	Edge protection Right-Angle 60/60	Edge protection Semi-Circular 40/40	Pipe protection Curvature 40	Pipe protection Curvature 60	Pipe protection Curvature 85	Surface protection Trapeze 40/40	Surface protection Semi-circular 40/32	Surface protection Rectangle 60/20
Delivery weight (kg/ea.)	0.7	0.5	0.8	0.7	1	2	2.5	0.7	0.7	0.7
Reference	422.23.243	422.24.979	422.25.253	422.20.276	422.21.293	422.22.247	422.20.581	422.26.582	422.27.977	422.20.678
Typical despatch time (working days)	1 / 2 days									