



Strong steel and aluminium construction ideal for restricting access to vans, commercial vehicles, caravans, motor-homes etc. to car-parks, traffic lanes etc.

This barrier can be easily rotated to allow access for authorised over-height vehicles, emergency vehicles etc. It is lockable in open or closed positions with triangular key, optional cylinder lock or locking pin secured by padlock (padlock not supplied)

Dimensions:

Support post: 100 x 100 x 3mm
 O/all height: 2,810mm
 Base plate: 295 x 295 x 10mm
 Drilled 6 fixing holes
 15mm Ø
 Aluminium cross-bar: 105 x 60mm
 Max. Headroom: 2,650mm
 Widths: 3,205 to 5,205mm



Adjustable heights: 2,200mm, 2,350mm, 2,500mm, 2,650mm.
 (Heights can be reduced further by up to 400mm with optional chain suspended nudge bar)

- Easily installed
- Restricts access
- Allows access to authorised vehicles
- Adjustable over 4 heights
- Strong construction

Options:

Can be supplied for permanent fixing in concrete.
 Cylinder lock.
 Locking pin secured by padlock (padlock not supplied).

We recommend that appropriate signage is used with this product.

| Description | Overall width (mm) | Max. drive trough width (mm) | Delivery weight (kg/ea.) | Reference | Typical despatch time (working days) |
|--|--------------------|------------------------------|--------------------------|------------|--------------------------------------|
| For Surface fix with triangular key | 3,205 | 3,000 | 55 | 305.27.817 | 15 / 20 days |
| | 3,705 | 3,500 | 60 | 305.22.859 | |
| | 4,205 | 4,000 | 65 | 305.23.208 | |
| | 4,705 | 4,500 | 70 | 305.22.147 | |
| | 5,205 | 5,000 | 75 | 305.22.810 | |

| Accessories | | | | | |
|---|--|--|--|------------|--------------|
| Root fixing adapter (2 pieces required) | | | | 222.22.548 | 15 / 20 days |
| Replacement triangular key | | | | 130.19.874 | |

COMPACT Aluminium Nudge Bar

The **COMPACT** Nudge Bar is an optional accessory for the **COMPACT** Access Height Restrictor. It is manufactured in Aluminium section size 60 x 30mm, in white with red reflective strips, and reduces the height of the Access Height Restrictor by up to 400mm. Includes two 6mm galvanised steel chains and connectors.



| Description | Dimensions (mm) | For widths (mm) | Delivery weight (kg/ea.) | Reference | Typical despatch time (working days) |
|-------------|-----------------|-----------------|--------------------------|------------|--------------------------------------|
| Aluminium | 2,000 | 3,000 - 5,000 | 8 | 305.21.100 | 15 / 20 days |

