

# START > TRAFFIC

EN ISO 20345:2011

D

TOURING **DEALER BOOT** 10349-01L

S3 SRC

Size: 36-48 Weight: 620 gr.

Working Environment:

Farming and Gardening, Logistics and Light Industry, Multipurpose, Building



### **Protection elements**



Toecap made of plastic, incredibly light and resistant to impact of over 200J, elastic.Not detected by metal detector. Non metal perforation resistant Insert to over 1100 N with a 3.0 mm truncated cone nail.Flexible and comfortable



Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater . stability.





resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.

## **FEATURES**

### UPPER

Greased Nubuk Dakar Leather Hydro

#### LINING

Soft Full Grain Leather Hydro 3D Air circulation 320 gr.

#### ANTISLIP LINING DUALMICRO

INSOLE Blow-fit 2.0

TOF CAP CTC- Composite Toe Cap


## **RESISTANCE TO PERFORATION**

Textile resistant to 3.0 mm nail - X Method

TYPE Ankle boot







# SOLE

**PU DUAL-DENSITY SRC** Two-component PU sole. Outsole suitable for indoor and outdoor use. Light and comfortable. Very flexible. Self-cleaning design and highly anti-slip. SRC Antislip Standard.

# TECHNOLOGIES

with the foot, transpiring, and comfortable. The E.V.A. HD perforad and thermoformed support ensures comfort and energy absorption

dynamic H control technology

houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.

WEL

Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.









Ergonomic rigid internal structure. It

**Electrical features** 

Wire Electricity Discharge





**Removable Insole** blow

> Anatomical and ergonomic removable insole with Flyfit, in direct contact