




Above: ref 916, Ø 600 mm

FRAMES

The thermoplastic resin frame is treated and tested against UV to avoid cracking and yellowing.



for wall or post

INSTALLATION

Multi-purpose mirrors are supplied with fully adjustable bolts and galvanised steel bracket kit for wall or post from 60 to 90mm in diameter. The kit allows the optimum orientation to be easily achieved.

The kit is robust and tested to withstand winds of up to 183 km/h.


POLYMRIR® QUALITIES

MAXIMUM VIEWING DISTANCE	OPTICS (mm)	PRODUCT CODE
5 metres	Ø 400 ●	514
7 metres	Ø 500 ●	515
9 metres	600 x 400 ■	524
11 metres	Ø 600 ●	516
15 metres	Ø 700 ●	517
20 metres	800 x 600 ■	526
20 metres	Ø 800 ●	518
30 metres	1000 x 800 ■	528



P.A.S® QUALITIES

MAXIMUM VIEWING DISTANCE	OPTICS (mm)	PRODUCT CODE
5 metres	Ø 400 ●	914
7 metres	Ø 500 ●	915
9 metres	600 x 400 ■	926
11 metres	Ø 600 ●	916
15 metres	Ø 700 ●	917
20 metres	800 x 600 ■	928
20 metres	Ø 800 ●	918
30 metres	1000 x 800 ■	9210



ACCESSORIES (see p. 50) These mirrors (excluding Ø 400 and Ø 500 mm) can accommodate a self-regulating heat film. Galvanised steel posts available for all models.