




Above: ref. 588, 800 x 600 mm






FRAMES

The thermoplastic resin frame is treated and tested against UV to avoid cracking and yellowing. It's adhesive tapes are durable and of high quality. The frames both Polymir®/PAS® mirrors in diameter 800 and 900 mm are in ABS/PMMA.

INSTALLATION



All mirrors are supplied with fully adjustable bolts and galvanised steel bracket kit for wall or round posts (Ø60 to 90mm) or rectangular posts (60x80mm or 80x80mm). The kit allows the optimum orientation to be easily achieved.

POLYMIR® QUALITIES

MAXIMUM VIEWING DISTANCE	OPTICS (mm)	FRAME (mm)	PRODUCT CODE
9 metres	600 x 400 	680 x 500	584
11 metres	Ø 600 	Ø 750	586
20 metres	800 x 600 	950 x 750	588



P.A.S® QUALITIES

MAXIMUM VIEWING DISTANCE	OPTICS (mm)	FRAME (mm)	PRODUCT CODE
9 metres	600 x 400 	680 x 500	984
11 metres	Ø 600 	Ø 750	986
20 metres	800 x 600 	950 x 750	988



ACCESSORIES (see p. 50) These mirrors can accommodate a self-regulating heat film. Galvanised steel posts available for all models.