

Alusthetic Drainage Inlet/Outlet Dimensions

	Low Profile End Cap With Outlet	Standard Profile End Cap With Outlet	Low Profile Connector With Outlet	Standard Profile Connector With Outlet	80mm - 110mm Rubber Coupling	50mm - 110mm Rubber Coupling	Gully Drain	Rubber Pipe Elbow
Inlet Internal Diameter	-	-	-	-	80mm - 85mm	48mm - 56mm	-	50mm
Inlet External Diameter	-	-	-	-	-	-	-	-
Outlet Internal diameter	-	-	-	-	112mm	110mm-122mm	-	50mm
Outlet External Diameter	40mm	50mm	75mm	85mm	-	-	75mm	-
Notes	Connect low profile channels to couplings and pipes from the end of the channel	Connect standard profile channels to adaptors and pipes from the end of the channel	Connect low profile channels to adaptors and other pipes from underneath	Connect standard profile channels to adaptors and other pipes from underneath	Fits around a standard 110mm diameter main sewage pipe to connect with an 80mm diameter pipe.	Fits around a standard 110mm diameter main sewage pipe to connect with a 50mm diameter pipe.	Both holes are designed to be used as outlets, running water from a downspout directly to the mains sewage	Designed to connect two 50mm pipes together. Can be used to connect end caps to pipes.