



Binley Shelter Galvanised Steel Frame Open Ended - Galvanised Sheet







The Binley shelter is a free-standing, open fronted shelter designed for on site assembly, constructed from galvanised mild steel. Complete with a 4mm UV stabilised PETG clear sheet roof, and side panels. Side-to side curved roof.

Width of 2m, with lengths from 1m-5m, extension bays can be added to achieve the desired shelter length.

Bolt down as standard.







Part Number	<u>Description</u>	Weight (kg)
138 000 522	Binley Shelter 1m	189kg
138 000 524	Binley Shelter 2m	281kg
138 000 526	Binley Shelter 3m	374kg
138 000 528	Binley Shelter 4m	466kg
138 000 530	Binley Shelter 5m	562kg
138 000 521	Binley Shelter 1m extension bay	
138 000 523	Binley Shelter 2m extension bay	
138 000 525	Binley Shelter 3m extension bay	
138 000 527	Binley Shelter 4m extension bay	
138 000 529	Binley Shelter 5m extension bay	

Product details

- Height 2095mm clearance, 2363mm overall
- Width 2074mm overall
- Length 1m, 2m, 3m, 4m, 5m and extensions

- Square flange plate 140mm x 140mm x 10mm
- Each flange plate requires 4 bolts
- 4mm UV stabilised PETG clear sheet panels

Installation & use

This product is guaranteed for 12 months (if installed and used correctly)

Each shelter leg requires bolting down to a suitable concrete surface, using expanding anchor bolts

The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes

On-site assembly requires construction skill









StartSafety.uk



sales@startsafety.uk





Binley Shelter Galvanised Steel Frame Open Ended - Galvanised Sheet

















01905 794 875



StartSafety.uk



sales@startsafety.uk

