
GFC3500 (Morpeth) 900mm Galvanised or Galvanised & Colour



The GFC3500 (Morpeth) Ornamental Mild Steel Bollard from AUTOPA is suitable for a wide range of locations and purposes. Constructed using mild steel, then galvanised to ensure its longevity. Cap and rings are welded onto the steel tube to complete the design.

Supplied concrete in as standard, bolt down and removable versions are also available.

The bollards are available in a galvanised and galvanised and coated finish (RAL numbers must be specified at time of order).

Eyelets, hooks and chains can be added to these bollards to complete the decorative effect.

(HEIGHT ABOVE GROUND)	
	FGL
(DEPTH BELOW GROUND)	
	(Ø114,3)

00

Part Number	Description	<u>Lift Weight (kg)</u>	<u>Weight (kg)</u>
138 120 301	Galvanised - Concrete In		13kg
138 120 302	Galvanised & Black - Concrete In		13kg
138 120 303	Galvanised & Colour - Concrete In		13kg
138 120 304	Galvanised - Bolt Down		13kg
138 120 305	Galvanised & Black - Bolt Down		13kg
138 120 306	Galvanised & Colour - Bolt Down		13kg
138 120 307	Galvanised - Removable	13kg	21kg
138 120 309	Galvanised & Black - Removable	13kg	21kg
138 120 308	Galvanised & Colour - Removable	13kg	21kg


Product details

- 900mm height above ground
- 114mm diameter
- 3mm wall thickness

- Concrete in 300mm (below ground)
- Price excludes fixing down bolts and padlock to secure
- Socket 300mm (below ground)

Installation & use

Bolt down to a suitable concrete surface. Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete.







StartSafety.uk

sales@startsafety.uk

