

## Mitre Top Bollard 900mm Above Ground 60mm - 168mm Diameter **Stainless Steel**

or parking in commun prestigious sites. Available in grade 30	A stainless steel as standard, this bollard is designed to remain with minimal upkeep.	(TUBE SIZE)	
Supplied ragged for o	casting in only.	RAGGED VERSION ONLY (DEPTH BELOW GROUND)	
Part Number 138 126 059 138 126 075 138 126 088 138 126 104 138 126 113 138 126 128	<u>Description</u> 60mm Stainless Steel - Concrete In 76mm Stainless Steel - Concrete In 89mm Stainless Steel - Concrete In 101mm Stainless Steel - Concrete In 114mm Stainless Steel - Concrete In 129mm Stainless Steel - Concrete In	<u>Weigh</u> 3k 4k 5k 6k 7k 7k	29 29 29 29

130 120 104		оку
138 126 113	114mm Stainless Steel - Concrete In	7kg
138 126 128	129mm Stainless Steel - Concrete In	7kg
138 126 142	139mm Stainless Steel - Concrete In	8kg
138 126 159	154mm Stainless Steel - Concrete In	9kg
138 126 171	168mm Stainless Steel - Concrete In	10kg

## **Product details**

- 900mm height above ground
- 2mm wall thickness

Concrete in 300mm (below ground)

## Installation & use

Bolt down to a suitable concrete surface. Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



## www.startsafety.uk +44 (0)1905 794875

Start Safety UK Drury Lane, Martin Hussingtree WR3 8TD

