



The AUTOPA RetractaPost-GL 500

The RetractaPost-GL offers a highly effective and robust way to protect premises and vehicles. The RetractaPost-GL is raised and lowered vertically. When raised the post is 500mm above ground, when lowered the post is fully below ground and covered using the integral lid. The post is lockable in the raised position by rotating the post 45° and then pressing the high-security push button 7-pin security lock. The post is unlocked using the supplied key, rotated and then lowered.

The RetractaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

Shown is 90mm version of the RetractaPost-GL 500.

Product Range

| Order Code | Description | Lift-up Weight | Weight |
|-------------|------------------------------|----------------|--------|
| 138 130 392 | 60mm (Galvanised) | 3.5kg | 14.4kg |
| 138 130 397 | 60mm (Galvanised and Colour) | 3.5kg | 14.4kg |
| 138 130 390 | 76mm (Galvanised) | 4.2kg | 15.1kg |
| 138 130 395 | 76mm (Galvanised and Colour) | 4.2kg | 15.1kg |
| 138 130 425 | 90mm (Galvanised) | 5.0kg | 23.5kg |

Accessories & installation parts

138 811 290 Spare key (please specify key number/product)

Product details

500mm Tall (When raised).
815mm Below Ground.
Mild Steel Galvanised Socket.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts. An excavated hole of approximately 900mm deep and 300mm diameter is required for installation. Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete. The lid of the post should be no more than 10mm above finished ground level. Keep the sliding post clean and occasionally lubricate the lock with Ambersil 40+ or similar. This product is guaranteed for 12 months (if installed and used correctly).

www.starttraffic.uk
01905 794875