



The RetractaPost-GL 745

The RetractaPost-GL offers a highly effective and robust way to protect premises and vehicles. The RetractaPost-GL is raised and lowered vertically. When lowered the post is fully below ground and covered using the integral lid. The post is lockable in the raised position by rotating the post 45° and then pressing the high-security push button 7-pin security lock. The post is unlocked using the supplied key, rotated and then lowered.

The RetractaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

Shown is 90mm version of the 90mm RetractaPost-GL 745 with optional Red & White chevron reflective label.

Product Range

Order Code	Description	Lift-up Weight	Weight
138 130 382	60mm (Galvanised)	4.6kg	17.6kg
138 130 387	60mm (Galvanised and Colour)	4.7kg	17.7kg
138 130 380	76mm (Galvanised)	5.5kg	18.5kg
138 130 385	76mm (Galvanised and Colour)	5.7kg	18.7kg
138 130 420	90mm (Galvanised)	6.6kg	30.2kg
138 130 422	90mm (Galvanised and Colour)	6.8kg	30.4kg
138 130 430	101mm (Galvanised)	9.3kg	40.0kg
138 130 432	101mm (Galvanised and Colour)	9.5kg	40.2kg

Accessories & installation parts

138 811 290	Spare key (please specify key number/product)
138 810 598	Red & White Chevron Reflective Label

Product details

745mm Tall (When raised).
1070mm Below Ground.
Mild Steel Galvanised Socket.
Grade 304 Stainless Steel Body.

Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts. An excavated hole of approximately 1,200mm deep and 300mm diameter is required for installation. Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete. The lid of the post should be no more than 10mm above finished ground level. Keep the sliding post clean and occasionally lubricate the lock with Ambersil 40+ or similar. This product is guaranteed for 12 months (if installed and used correctly).

www.starttraffic.uk
01905 794875