



### The RetractaPost-GL 900

The RetractaPost-GL 900 offers a highly effective and heavy duty way to protect premises and vehicles. The RetractaPost-GL 900 is 900mm above ground when raised. Due to the heavy weight of the post, it incorporates our lift assist system, which greatly reduces the lift up weight of the product and controls the post when lowering (114mm is available with or without lift assist).

When lowered the post is fully below ground and covered using the integral lid. The post is lockable in the raised position by rotating the post 45° and then pressing the high-security push button 7-pin security lock. The post is unlocked using the supplied key, rotated and then lowered. The RetractaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.

Shown is the 114mm RetractaPost-GL with optional Red & White chevron reflective label.

#### Product Range

Order Code	Description	Lift-up Weight	Weight
138 130 440	114mm (Galvanised)	12.0kg	47.0kg
138 130 441	114mm (Galvanised and Colour)	12.0kg	47.0kg
138 130 450	114mm (Galvanised with Lift Assist)	4.0kg (approx.)	50.4kg
138 130 452	114mm (Galvanised and Yellow with Lift Assist)	4.0kg (approx.)	50.4kg
138 130 460	139mm (Galvanised with Lift Assist)	6.0kg (approx.)	62.0kg
138 130 462	139mm (Galvanised and Yellow with Lift Assist)	6.0kg (approx.)	62.0kg
138 130 470	168mm (Galvanised with Lift Assist)	8.0kg (approx.)	65.5kg
138 130 473	168mm (Galvanised and Colour with Lift Assist)	8.0kg (approx.)	65.5kg

#### Accessories & installation parts

138 811 290	Spare key (please specify key number/product)
138 810 598	Red & White Chevron Reflective Label

#### Product details

900mm Tall (When raised).

1250mm Below Ground.

Galvanised or galvanised and coated finish.

#### Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts.

An excavated hole of approximately 1,400mm deep and 300mm diameter is required for installation. Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete.

The lid of the post should be no more than 10mm above finished ground level.

Keep the sliding post clean and occasionally lubricate the lock with Ambersil 40+ or similar.

This product is guaranteed for 12 months (*if installed and used correctly*).

**www.starttraffic.uk**  
**01905 794875**