



## Bedford Shelter - Galvanised Galvanised Steel Frame Open Sided







The Bedford shelter is a free-standing, open sided shelter designed for on site assembly, constructed from galvanised mild steel. Complete with galvanised sheet flat angled roof.

Suitable as a cycle shelter or walkway. Width of 2m, with lengths from 1m-5m, extension bays can be added to achieve the desired shelter length.

Bolt down as standard.



Part Number	<u>Description</u>	Weight (kg)
138 204 650	Bedford Shelter 1m	160kg
138 204 651	Bedford Shelter 2m	202kg
138 204 652	Bedford Shelter 3m	243kg
138 204 653	Bedford Shelter 4m	285kg
138 204 654	Bedford Shelter 5m	326kg
138 204 655	Bedford Shelter 1m extension bay	
138 204 656	Bedford Shelter 2m extension bay	
138 204 657	Bedford Shelter 3m extension bay	
138 204 658	Bedford Shelter 4m extension bay	
138 204 659	Bedford Shelter 5m extension bay	

## **Product details**

- Height 2168mm clearance, 2527mm overall
- Width 2159mm overall
- Length 1m, 2m, 3m, 4m, 5m and extensions

- Square flange plate 200mm x 200mm x 8mm
- Each flange plate requires 4 bolts
- 1mm galvanised steel panels

## Installation & use

This product is guaranteed for 12 months (if installed and used correctly)

Each shelter leg requires bolting down to a suitable concrete surface, using expanding anchor bolts

The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes

On-site assembly requires construction skill



www.autopa.co.uk +44 (0)1788 550556







## Bedford Shelter - Galvanised Galvanised Steel Frame Open Sided













www.autopa.co.uk +44 (0)1788 550556

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP

