



01905 794 875  
 StartSafety.uk  
 sales@startsafety.uk



**2471**

GECKO SAFETY SHOE

0050 0050  
 5499 Orange/Black  
 2-13

**FUNCTIONALITY:** Freehook. Padded shaft edge. ESD approved (confirms with IEC 61340-5-1). Heel reinforcement. Oil resistant outsole. Toe reinforcement. Heat resistant outsole. Water repellent. **UPPER MATERIAL:** Textile. **FIT:** Wide. **NAIL PROTECTION MATERIAL:** Textile PS. **TOECAP MATERIAL:** Composite. **SOLE MATERIAL:** PU midsole, nylon shank, Nitrile outsole. **LINING MATERIAL:** Polyester. **INSOLE MATERIAL:** Textile, soft PU. **SHOE SIZE:** 35-48. **CERTIFICATION:** EN ISO 20345:2011 S3 SRC HRO ESD.



**2471**

GECKO SAFETY SHOE

9935 Black/Yellow, 9956 Black/Red  
 2-13

**FUNCTIONALITY:** Freehook. Padded shaft edge. ESD approved (confirms with IEC 61340-5-1). Heel reinforcement. Oil resistant outsole. Toe reinforcement. Heat resistant outsole. Water repellent. **UPPER MATERIAL:** Microfiber. **FIT:** Wide. **NAIL PROTECTION MATERIAL:** Textile PS. **TOECAP MATERIAL:** Composite. **SOLE MATERIAL:** PU midsole, nylon shank, Nitrile outsole. **LINING MATERIAL:** Polyester. **INSOLE MATERIAL:** Textile, soft PU. **SHOE SIZE:** 35-48. **CERTIFICATION:** EN ISO 20345:2011 S3 SRC HRO ESD.



**2472**

GECKO SAFETY SHOE

9935 Black/Yellow, 9956 Black/Red  
 2-13

**FUNCTIONALITY:** Freehook. Padded shaft edge. ESD approved (confirms with IEC 61340-5-1). Heel reinforcement. Oil resistant outsole. Toe reinforcement. Heat resistant outsole. Water repellent. Breathable insole. **UPPER MATERIAL:** Textile. **FIT:** Wide. **NAIL PROTECTION MATERIAL:** Textile PS. **TOECAP MATERIAL:** Composite. **SOLE MATERIAL:** PU midsole, nylon shank, Nitrile outsole. **LINING MATERIAL:** Polyester. **INSOLE MATERIAL:** Textile, soft PU. **SHOE SIZE:** 35-48. **CERTIFICATION:** EN ISO 20345:2011 S1 PSRC HRO ESD.



**2475**

GECKO SAFETY SHOE

9935 Black/Yellow, 9956 Black/Red  
 2-13

**FUNCTIONALITY:** Padded shaft edge. ESD approved (confirms with IEC 61340-5-1). Heel reinforcement. Metal free. Oil resistant outsole. Toe reinforcement. Heat resistant outsole. Water repellent. Breathable insole. **UPPER MATERIAL:** Microfiber. **FIT:** Wide. **NAIL PROTECTION MATERIAL:** Textile PS. **TOECAP MATERIAL:** Composite. **SOLE MATERIAL:** PU midsole, nylon shank, Nitrile outsole. **LINING MATERIAL:** Polyester. **INSOLE MATERIAL:** Textile, soft PU. **SHOE SIZE:** 35-48. **CERTIFICATION:** EN ISO 20345:2011 S3 SRC HRO ESD.



**2473**

GECKO SAFETY BOOT

9935 Black/Yellow, 9956 Black/Red  
 2-13

**FUNCTIONALITY:** Freehook. Padded shaft edge. ESD approved (confirms with IEC 61340-5-1). Heel reinforcement. Oil resistant outsole. Toe reinforcement. Heat resistant outsole. Water repellent. Breathable insole. **UPPER MATERIAL:** Microfiber. **FIT:** Wide. **NAIL PROTECTION MATERIAL:** Textile PS. **TOECAP MATERIAL:** Composite. **SOLE MATERIAL:** PU midsole, nylon shank, Nitrile outsole. **LINING MATERIAL:** Polyester. **INSOLE MATERIAL:** Textile, soft PU. **SHOE SIZE:** 35-48. **CERTIFICATION:** EN ISO 20345:2011 S3 SRC HRO ESD.



**ANTI-STATIC PROPERTIES AND ESD**

All safety footwear in the Blåkläder range is antistatic. In addition, we offer footwear that is verified as ESD products. Both antistatic and ESD properties are evaluated in order to prevent electrostatic discharge. However, there is an important difference; the antistatic specification in the EN ISO 20345 standard is designed to protect the person wearing the footwear, while the requirements of the ESD standards (IEC61340-5-1) are designed to protect the product being handled by the person wearing the footwear.

Blåkläder's ESD safety footwear is approved by RISE, Research Institutes of Sweden; [www.ri.se/en](http://www.ri.se/en)

