



DataSheet

The trusted go-to brand for fire extinguishers in the UK, Commander offers a comprehensive range of fire extinguishers. Now PFAS free across the entire range, time has proven the Commander range of fire extinguishers as a dependable choice for almost any situation – with reliable performance guaranteed.

CO₂ FIRE EXTINGUISHERS

As well as being suitable for Class B (flammable liquid) fires, CO₂ fire extinguishers are the ideal choice for installation in electrical fire risk settings because it won't damage electrical equipment or machinery.

The 2kg and 5kg Commander CO₂ are among the finest on the market, while the Commander Renovate range are a cost effective and economical solution.

Technical Specification	FX-CO2-002-DCF	FX-CO2-005-DCF	FX-CO2-002-ECF	FX-CO2-005-ECF
Capacity	2kg	5kg	2kg	5kg
Fire Rating	34B	70B	34B	70B
Extinguishing Medium	CO ₂	CO ₂	CO ₂	CO ₂
Working Pressure	56 bar @ 20°C	56 bar @ 20°C	56 bar @ 20°C	56 bar @ 20°C
Temperature Range	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C
Cylinder Material	Aluminium	Aluminium	Steel	Steel
Pressuring Gas	-	-	-	-

029 2086 8333

029 2085 0627

sales@checkfire.co.uk

www.CheckFire.co.uk



PRODUCT CODE

FX-CO2-002-DCF | FX-CO2-005-DCF |
FX-CO2-002-ECF | FX-CO2-005-ECF

PRODUCT GROUP

CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter)

FX-CO2-002-DCF: 585 x 165 x 105
FX-CO2-005-DCF: 760 x 180 x 140
FX-CO2-002-ECF: 580 x 175 x 185
FX-CO2-005-ECF: 760 x 180 x 140

WEIGHT

FX-CO2-002-DCF: 6.18kg
FX-CO2-005-DCF: 13.4kg
FX-CO2-002-ECF: 6.3kg
FX-CO2-005-ECF: 11.28kg

- Kitemarked to BS EN3*
- UKCA and CE approved
- Supplied with Frost free/Safe horn***
- Corrosion-resistant finish
- Full range of spare parts available
- 5-year warranty

*Excluding the FX-CO2-002-ECF & FX-CO2-005-ECF

**Horns not supplied with Renovates and will need to be ordered separately

*** Only applies to FX-CO2-002-DCF & FX-CO2-005-DCF

