



Data Sheet

Market-leading Commander® has something new to offer - CommanderEDGE. BS EN3 Kitemark approved across the range, it has become the choice of the professional, with a reassuring mixture of performance, quality and value. The range includes Water, Foam, CO₂ and Powder units and offers solutions for almost all situations. The internationally recognised BS Kitemark is assurance of dependable design and manufacture.

PLAIN WATER FIRE EXTINGUISHER

A water-based fire extinguisher is a popular choice for Class A fires (combustible materials). Water fire extinguishers work by cooling the fuel and ensuring it burns at a much slower pace until the fire is extinguished. With a low cost price, ease of maintenance and the fact they're an environmentally friendly option, it's easy to see why water fire extinguishers are a preferred choice for many businesses.

Technical Specification	FX-PWA-006-DCF	FX-PWA-009-DCF
Capacity	6ltr	9ltr
Fire Rating	21A	27A
Extinguishing Medium	Plain Water	Plain Water
Working Pressure	12 bar @ 20°C	12 bar @ 20°C
Temperature Range	+5-+60°C	+5-+60°C
Cylinder Material	Steel	Steel
Pressuring Gas	Nitrogen	Nitrogen

029 2086 8333

sales@checkfire.co.uk

029 2085 0627

www.CheckFire.co.uk



COMMANDEREDGE

PRODUCT CODE

FX-PWA-006-DCF | FX-PWA-009-DCF

PRODUCT GROUP

CommanderEDGE Extinguishers

DIMENSIONS (mm) (height x width x diameter)

FX-PWA-006-DCF: 539 x 295 x 158

FX-PWA-009-DCF: 610 x 325 x 193

WEIGHT

FX-PWA-006-DCF: 9.38kg

FX-PWA-009-DCF: 14.5kg

- Kitemarked to BS EN3
- MED/MER approved
- Corrosion resistant finish
- Plastic base skirt for protection
- 5 year warranty

