

Specification sheet: Cresco 10SWG



Product Description:
Impellor Style Pedestrian operated spreader

	Descriptions	Technical Specification
	Framework	Powder coated steel with strong tubular backstand
	Wheels	2 X moulded tread wide wheels 24 cm high by 7 cm across
	Axle	Powder coated steel
	Gear box	Encased crown and pinion, zero maintenance gears. Made from composite material, hard-wearing construction with extra-large bushings
	Hopper	30 litre capacity. Up to maximum 35kg weight bearing, 3 drop hole
	Impellor	Shaped 21cm four fin impellor. Provides spread width of between 2.5 and 6 metres
	Shutter Plate (Summer Slider)	Hard wearing multifunctional interchangeable slider. Offering left and right spread pattern adjustment and a border control system
	Shutter Plate (Winter slider)	Hard wearing multifunctional interchangeable slider. Providing high output and spread width reduction system
	Linkage	Solid steel rod
	Agitator	Pin through agitator
	On/off Control Bezel	1 to 20 scale with T bar style lever, with rate setting lock
	Handlebar	Cushioned grip over loop style easy fold away handle
	Weight Empty	5.5 kg
	Assembled Product Dimensions	Width 45cm Height 89cm Length 85 cm
	Packaging	Assembled in corrugated cardboard box.
	Pallet Dimensions	UK: 120cm(L)x100cm(W)x200cm(H) EU: 120cm(L)x80cm(W)x200cm(H)
	Box dimensions and weights	65cm by 51cm by 41cm 6.25kg
	Pallet configuration (units per pallet)	UK - 18 units EU - 10 units
	Guarantee/Warranty	3-Year limited warranty
	Box information	QR code and Bar code, full instruction and how to use manual. Available in different languages upon request.