

Specification sheet: Cresco 30SWP



Product Description:
Impellor Style Pedestrian operated spreader

	Descriptions	Technical Specification
	Framework	Powder coated with stainless fasteners
	Wheels	2x Pneumatic treaded tyres with inner tubes 13 x 5.00 - 6
	Axle	Stainless steel
	Gear box	Encased crown and pinion, zero maintenance gears. Manufactured in a composite material, ultra-hard-wearing construction with advanced performing bushings
	Hopper	40 litre capacity with front lift point, up to a maximum 45kg weight bearing. 3 drop hole outlets
	Impellor	24 cm shaped four fin impellor provides spread widths of between 2.5 and 6 metres
	Shutter plate (Summer Slider)	Hard wearing multifunctional interchangeable slider. Providing left & right side spread pattern adjustments and a border control system
	Shutter plate (Winter slider)	Hard wearing multifunctional interchangeable slider. Providing high output, wide spread and spread width reduction system
	Linkage	Solid steel rod
	Agitator	New oscillating spider type, providing superior material movement and reduced drag
	On/off control bezel	1 to 20 scale with T bar style lever and rate setting lock mechanism
	Handlebar	Dual shaft connecting to bull horn style handle with cushion grips for ultimate user comfort
	Weight empty	14 kg
	Assembled Product Dimensions	Width 60 cm height 121 cm length 76 cm
	Packaging	Assembled in a corrugated cardboard box
	Pallet Dimensions	UK: 120cm(L)x100cm(W)x200cm(H) EU: 120cm(L)x80cm(W)x200cm(H)
	Box dimensions and weight	Semi assembled 65cm by 60cm by 60cm 14.8 kg
	Pallet configuration (units per pallet)	UK - 6 Units EU - 6 Units
	Guarantee/warranty	3-year limited warranty
	Box information	QR code and Bar code, full instruction and how to use manual. Available in different languages upon request.