

Specification sheet: Cresco 30SWS



Product Description:
Impellor Style Pedestrian operated spreader

	Descriptions	Technical Specification
	Framework	Stainless steel with stainless fasteners
	Wheels	2x Pneumatic treaded tyres with inner tubes 13 x 5.00 – 6
	Axle	Stainless steel
	Gear box	Encased crown and pinion, zero maintenance gears. Manufactured in a composite material, ultra-hard-wearing construction with enhanced performance bushings
	Hopper	40 litre capacity with front lift point, up to a maximum 45kg weight bearing. 3 drop hole outlets
	Impellor	Shaped 24.0 cm four fin impellor. Provides spread width of between 2.5 and 6 metres
	Shutter plate (Summer Slider)	Hard wearing multifunctional interchangeable slider. Providing left & right side spread pattern adjustments and a border control system
	Shutter plate (Winter slider)	Hard wearing multifunctional interchangeable slider. Providing high output, wide spread and spread width reduction system
	Linkage	Solid steel rod
	Agitator	New oscillating spider type, providing superior material movement and reduced drag
	On/off control bezel	1 to 20 scale, with T bar style lever and rate setting lock mechanism
	Border Control Lever	1 - 20 scale, with T bar style lever
	Handlebar	Dual shaft to bull horn style handle with cushion grips for ultimate user comfort
	Weight empty	12 kg
	Assembled Product Dimensions	Width 60cm Height 121cm Length 76cm
	Packaging	Assembled in a corrugated cardboard box
	Pallet Dimensions	UK: 120cm(L)x100cm(W)x200cm(H) EU: 120cm(L)x80cm(W)x200cm(H)
	Box dimensions and weight	Semi-assembled 65cm by 60cm by 60cm 12.3 kg
	Pallet configuration (units per pallet)	UK - 6 Units EU - 6 Units
	Guarantee/warranty	3-year limited warranty
	Box information	QR code and Bar code, full instruction and how to use manual. Available in different languages upon request.