

# TECHNICAL SPECIFICATION



## FilterSpec® Pro

FilterSpec® Pro Black/Clear FFP3V / AGE130-201-100



### DESCRIPTION

Worn together, safety eyewear and respirators often reduce each other's effectiveness because eyewear frames compromise the seal of the respirator and lead to lens misting and reduced respiratory protection. FilterSpec®Pro combines both protective devices into an integrated unit.

### OPTIONS

FilterSpec® Pro Black/Clear FFP2V (AGE120-201-100)  
**FilterSpec® Pro Black/Clear FFP3V (AGE130-201-100)**

### SAFETY STANDARDS

EN 170 • EN 149 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 23 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

	Face Fit Testing Required <b>Yes</b>		LIGHT TRANSMISSION BREAKDOWN Lens Shade number <b>2C</b>
	LIGHT TRANSMISSION BREAKDOWN Lens Shade number <b>1.2</b>		Manufacturer's Trademark <b>JSP Dagger</b>
	Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) <b>1</b>		Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles. <b>B</b>
	The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional <b>T</b>		Protection from Liquid Droplets <b>3</b>
	Protection from Large Dust Particles (up to 40 um grain size) <b>4</b>		Resistance to Molten Metals and Hot Solids (optional) <b>9</b>
	Classification <b>FFP3 (Filtering Facepiece Particulate)</b>		Filter Type <b>P (Protects against solid and liquid aerosols)</b>
	Usage <b>NR (Non-reusable)</b>		Activated Carbon Layer <b>No</b>
	Minimum Filtration Efficiency <b>99% for FFP3 Rated</b>		Maximum Total Inward Leakage (TIL) <b>2%</b>
	Nominal Protection Factor <b>50</b>		UK Assigned Protection Factor <b>20</b>
	Mask Design <b>Moulded</b>		Exhalation Valve <b>Yes</b>
	Mask Material <b>Polypropylene</b>		Material <b>Polycarbonate lens</b>
	Material <b>HDPE mask holder</b>		Filter Shelf Life <b>5 years</b>
	BSI Kitemark <b>Yes</b>		Product Weight <b>144g</b>

## FEATURES




### Integration

FilterSpec's unique design overcomes the problem of ill fitting masks, fogged lenses and non-conformity that can often occur when one item of PPE compromises another.



### Quality Lens

The FilterSpec® Pro goggle features a 5.5 base curve lens. FilterSpec® lenses have a base curve of 6.5. Both offer optimal coverage and feature anti-mist and anti-scratch lens coatings.



### Efficient Filter

The easily replaced filters are made from three layers for exceptional performance. Available with low resistance exhalation valve to reduce moisture and CO2 build-up.

## RANGE

## DOWNLOADS



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 23 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





 [Image Pack \(ZIP\)](#)

 [doc-filterspec-pro-ffp3-mask.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 23 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

