



flame retardant - Stretch Zones MASCOT® ACCELERATE MULTISAFE



S	M	L	XL	2XL	3XL	4XL
5XL						

Main material/upper material

21509-281 Jacket

44% modacrylic/30% cotton/20% polyamide/5% aramid/1% carbon fibres 260 g/m²











Ripstop.Impregnation is required after each wash to maintain EN 13034 protection.

Industrial care category B1

Certifications













- **OEKO-TEX® STANDARD 100**
- EN 1149-5
- EN ISO 11612 (A1, A2, B1, C1, E1, F1)
- EN 13034 (Type 6)
- EN 13034, category J
- EN 61482-1-2 APC 1 (front & sleeves APC2)
- EN IEC 61482-1-1 (ELIM 7,7 cal/cm2, ATPV 9,5 cal/cm2, front and sleeves ELIM 22 cal/cm², ATPV 28 cal/cm²)
- ProWash®

Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.

Logo placement:

Workwear logo. Special placement. Contact to discuss further





- A high level of protection with anti-static, acid protection and flame retardant properties.
- Protects from electric arcs.
- The combination of firm fabric and stretch gives you an added freedom of movement.
- Zipper closure and double storm flap with magnet fastening.
- The quick release zip allows you to open the zip fastener quickly.
- Strap for gas alarm.
- Suitable for Industrial Laundering.

Technical info

Anti-static, acid-protective and flame retardent. Protects from electric arcs. Stretch fabric on parts of the product. High collar. Quick release zipper closure and double storm flap with magnet closure. Strap for gas alarm. Chest pockets with zip. Prepared for attachment of ID card. Front pockets with a zip. Elastic at cuffs and waist. With print effects.

User

