




06609-135 Jacket

multi-protective

MASCOT® MULTISAFE



XS	S	M	L	XL	2XL	3XL
4XL						

Main material/upper material

87% cotton/12% polyamide/1% carbon fibres
320 g/m²




Canvas structure. Up to 7% shrinkage by 5x industrial washes (ISO 15797) and up to 5% by domestic washes. Wash separately. Fluorocarbon impregnation is required after each wash to maintain EN 13034 protection.

Industrial care category B2

PYROPRO®

Certifications



- OEKO-TEX® STANDARD 100
- EN 1149-3
- EN 1149-5
- EN 13034 (Type 6)
- EN ISO 11612 (A1, B1, C1, E1)
- EN 61482-1-1 (ATPV - 12 cal/cm²)
- EN 61482-1-2 APC 1
- EN ISO 11611 - class 1 (A1)



- Anti-static, acid-resistant and flame-retardant PyroPro®.
- Durable triple stitched seams that extend the product life.
- Fastening with storm flap and hidden press studs, so as not to scratch the surroundings.
- Seams face downwards so sparks can not get lodged in them.

Technical info

Anti-static, acid-protective and flame retardent PyroPro®. Protects from electric arcs and occasional welding arcs. The surface treatment makes the product dirt-repellent. High collar with press studs. Triple stitched seams on sleeves, shoulders and at the sides. Fastening with hidden press studs. Chest pockets with flap and hidden press studs. Front pockets with hidden zip. Inner pocket with flap. Cuffs with elastic. Seams face downward so sparks can not get lodged in. Contrast stitching.

User



Logo

Due to the unique properties of the fabric, logo printing is only available through the use of specific transfer types. As this is a safety product, we strongly recommend that MASCOT affix the logo to reduce the risk of errors. Please contact customer service for further information.

Logo placement:

- Workwear logo. Special placement. Contact to discuss further