

**P5-STEEL355**



IDEALLY SUITED     UNSUITABLE  
 OCCASIONAL USE



MATERIALS	
ALUMINIUM	<input type="checkbox"/>
ANGLE IRON	<input checked="" type="checkbox"/>
CARBON STEEL	<input checked="" type="checkbox"/>
CAST IRON	<input type="checkbox"/>
FIBREGLASS	<input type="checkbox"/>
HIGH NICKEL ALLOYS	<input type="checkbox"/>
PLASTIC	<input type="checkbox"/>
PAINT REMOVER	<input type="checkbox"/>
RUST REMOVER	<input type="checkbox"/>
SHEET METAL	<input type="checkbox"/>
STAINLESS STEEL	<input type="checkbox"/>
STEEL BOX SECTIONS	<input checked="" type="checkbox"/>
STRUCTURAL STEEL	<input checked="" type="checkbox"/>

**DESCRIPTION:**

The P5-STEEL355 is a 66 teeth TCT blade for use on low revving chop saws, to cut mild steel materials, such as threaded rod, hollow sections, solid sections, angle iron and pipes.

**FEATURES:**

- Fast
- Clean cut
- Consistent depth of cut
- Up to 40 times the life of an abrasive disc

**MACHINE SUITABILITY:**

EVOSAW 355 and other low revving chop saws.

**USER TIPS:**

- Always ensure that the blade is suitable for your machine type. Using a blade designed for another machine type could be unsafe
- Do not exceed the discs 1600rpm maximum speed
- Make certain that the blade is suitable for the material being cut
- Do not force the cut. Let the blade and machine do the work.

**PART NO.    DIMENSIONS**

GT11100    355 x 2.4 x 2.0 x 25.4mm x 66 teeth

**PACKAGING DETAILS:**

White corrugated cardboard box.

