

## P6-ATD



Manufactured to EN13236

HARD EXTERIOR PORCELAIN

HARD INTERIOR PORCELAIN

STONE TILE GRANITE

SOFT FILLED CERAMIC



### DESCRIPTION:

Our range of auto-cool diamond tile drills are filled with a lubricating wax. During the drilling process the leading edge of the wax melts and autocools the diamonds, meaning there is no need to apply a secondary coolant, such as water. With hexagonal fitting for use in cordless and corded drills.

### FEATURES:

- Fully exposed diamond joined by a vacuum process
- A wax lubricant - injected into the hollow centre of the bit
- Aids smaller diameters
- Smooth and speedy experience.

### MACHINE SUITABILITY:

Cordless and corded drills.

### STANDARDS:

EN13236: European Standard that regulates the safety requirements for super abrasive (diamond) products.

### USER TIPS:

- Mark the tile and place the drill tip at a 45-degree angle
- Start drilling and level the drill once the tile surface is scored
- Drill using a slight oscillating motion until the hole is complete
- Do not use unnecessary pressure, the weight of the machine is sufficient
- Use at speeds between 800 - 2000rpm
- For harder tiles use a slower rpm / for softer tiles use a faster rpm.

### PART NO. DIMENSIONS

DP19000	5 x 67mm
DP19005	6 x 67mm
DP19010	7 x 67mm
DP19015	8 x 67mm
DP19020	10 x 80mm
DP19025	12 x 80mm

### PACKAGING DETAILS:

Full colour corrugated cardboard box.



IDEALLY SUITED  UNSUITABLE  
 OCCASIONAL USE

### MATERIALS

ALUMINIUM	
ASPHALT	
ASPHALT OVER CONCRETE	
BRICKS - CLASS A ENGINEERING	
BRICKS - CLASS B ENGINEERING	
BRICKS - STANDARD FACING BRICKS	
CEMENT FIBRE BOARD	
CAST IRON	
CLAY PRODUCTS	
COMPOSITE CLADDING & PANELS	
CONCRETE - BEAMS, KERBS, PIPES & SLABS	
CONCRETE - BLOCK PAVING	
CONCRETE - FLAG STONES	
CONCRETE - FLINT AGGREGATE	
CONCRETE - GENERAL PURPOSE	
CONCRETE - GREEN (up to 24 Hours Old)	
CONCRETE - HEAVY STEEL REINFORCEMENT	
CONCRETE - LIGHT STEEL REINFORCEMENT	
CONCRETE - ROOF TILES	
CONCRETE BLOCKS - LIGHTWEIGHT 3 TO 7 NEWTON	
CONCRETE BLOCKS - MEDIUM DENSITY 7 TO 12 NEWTON	
CONCRETE BLOCKS - SOLID DENSITY 12+ NEWTON	
CEMENT SCREED	
EARTHSTONE WORKTOPS	
FIBREGLASS	
GLASS REINFORCED PLASTIC (GRP)	
GRANITE - BLOCKS & WORKTOPS	
GRITSTONE	
GROUNDWORK - HARD SOIL	
LAMINATED PRODUCTS	
LIMESTONE	
MARBLE - BLOCKS & WORKTOP	
MORTAR RAKING	
PLASTIC (PVC, PE, PP, PC & COMPOSITES)	
QUARTZ WORKTOPS	
RUBBER	
RAILWAY SLEEPERS	
SANDSTONE - ABRASIVE	
SANDSTONE - INDIAN	
STEEL SECTION - PIPES & BARS	
TILES - CERAMIC	
TILES - GRANITE	
TILES - LIMESTONE	
TILES - MARBLE	
TILES - PORCELAIN	
TILES - 20mm EXTERIOR PORCELAIN	
TILES - SLATE	
TREE ROOTS	
WOOD	
YORK STONE	