

**P6-FDC**



IDEALLY SUITED     UNSUITABLE  
 OCCASIONAL USE



**CONICAL FLAP DISC  
TYPE 29 - CERAMIC**



- Conical flap discs have angled flaps to improve comfort of use on contoured and edge work
- The 10° angle of the flaps greatly increases the surface contact for improved stock removal on flat surfaces
- For an optimum performance of speed and stock removal, grind at angles between 15° and 25°

ALUMINIUM	<input type="checkbox"/>
ANGLE IRON	<input checked="" type="checkbox"/>
CARBON STEEL	<input checked="" type="checkbox"/>
CAST IRON	<input checked="" type="checkbox"/>
FIBREGLASS	<input checked="" type="checkbox"/>
HIGH NICKEL ALLOYS	<input type="checkbox"/>
PLASTIC	<input checked="" type="checkbox"/>
PAINT REMOVER	<input checked="" type="checkbox"/>
RUST REMOVER	<input checked="" type="checkbox"/>
SHEET METAL	<input checked="" type="checkbox"/>
STAINLESS STEEL	<input checked="" type="checkbox"/>
STEEL BOX SECTIONS	<input checked="" type="checkbox"/>

**DESCRIPTION:**

Professional type 29, conical ceramic flap discs. The special, non-fused, ceramic aluminium oxide gives a noticeable increased life and superior performance when compared to that of a zirconium disc, and is suitable for use on stainless and mild steel, as well as other tensile alloys.

**PRODUCT DETAILS:**

PART NO.	TYPE	SPECIFICATION	DIMENSIONS	PACK QTY.
AP10233	T29	C80	115 x 22.2mm	10
AP10234	T29	C120	115 x 22.2mm	10

**FEATURES:**

- Reduced vibration and noise compared to a conventional grinding disc
- Smooth consistent finish
- Lightweight fibreglass backing
- High grade ceramic grain for increased life and performance

**MACHINE SUITABILITY:**

Electric and cordless angle grinders.

**STANDARDS:**

EN13743: European standard that regulates the safety requirements for coated abrasive products. (Sanding sheets and discs.)

**USER TIPS:**

For optimum performance of speed and stock removal, grind at angles between 15° and 25°.

**PACKAGING DETAILS:**

Full colour corrugated cardboard box.

