

SMALRITMEHTY

VERSATILE & ROBUST MINI BARRIER

The Portagate[™] is a blow moulded high density polyethylene barrier, supplied as a 3 or 4 gate system. Light and compact, the Portagate™ is designed to meet communications industry requirements and enables increased quantities per vehicle.











PORTAGATE™ FEATURES

CONFIGURATIONS

• Adjoining clips allow multi positioning configurations to be formed such as a triangle, a square, or a single line.



PORTAGATE™ BARRIER SYSTEM		
DIMENSIONS	Weight	2kg (Single gate)
	Height	1000mm
	Width	750mm
STANDARDS		CH8 and Street Works Act BS 8442 (reflective only)
MATERIAL	Body	Polyethylene
	Feet	Recycled PVC



FIRM HOLD

 By sliding the top hinge clip up and down, the orientation of the panels can be locked in position to ensure added rigidity.




ADDED STABILITY

- Designed to accept anti-trip recycled feet for increased stability.
- Should there be an occurrence of broken feet, we will supply replacements at no extra cost!* "Subject to terms of "Surefoot" guarantee.




TEMPORARY SIGNAGE

• Recesses are included for toggle mounted courtesy signs to enable the system to be fully closed with the signs still attached.



REFLECTIVE PANEL

- Class R1 high intensity reflective.
- 20% more reflectivity than standard lower grade reflective material.
- Conforms to EN12899-1



STACKABLE

- Can be stacked open in any 180° orientation.
- Pallet stacking height is 20 units for 4 gate systems and 25 units for 3 gate systems.



BRANDING

- One-piece mould can be made in any colour to match a brand.
- Contractor details can be embossed and highlighted at the front of the barrier.





Start Traffic Ltd