



EN ISO 20345:2022



HELEVO  
**XENO BOA®**  
**66547-00L**

**S3S FO SR**

**Size:** 35-48  
**Weight:** 510 gr.

**Fit:** 11

**Working Environment:**  
Multipurpose, Logistics and Light Industry, Components and Automotive, ESD Areas



## FEATURES

### UPPER

No ladder, recycled Knit textile

### LINING

3D Green Air 320 gr.

### ANTISLIP LINING

DUALMICRO

### INSOLE

TALENT FIT D3O

### TOE CAP

Nano Toe SXT

### RESISTANCE TO PERFORATION

KK7 Antiperforation recycled PS

### TYPE

Low Shoe

### SOLE

#### PU DUAL-DENSITY CCYCLED® SR

Two-components PU sole, Outer- and in-between sole with ESD compound. With recycled material Ccycled®, highly non-slip SR Antislip standard.

#### Boa® lace length

L6 - 65cm

## TECHNOLOGIES

### Removable Insole



Breathable anatomic insole. Durable recycled fabric with open cell foam. Absorbs shocks and decreases fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use.



### Protection elements



Composite toe cap, reinforced with carbon nanotubes. Resistant > 200J Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable.



### Lateral stability

**dynamicHC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



### Torsional stability

**STABIL•ACTIVE**

Support made of rigid plastic material. It stabilizes the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



### Electrical features



ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

### Other



**FIT TO GO FURTHER™**

A patented closing system with a multi coated stainless steel cable. The BOA® Fit System delivers micro-adjustable precision fit, engineered to perform in the toughest conditions.



### PU - PU

SOLE 66

### SLIP RESISTANCE

EN ISO 20345:2022

#### BASIC CERAMIC WITH NALS

|                        |        |      |
|------------------------|--------|------|
| FORWARD HEEL SLIP      | ≥ 0.31 | 0,47 |
| BACKWARD FOREPART SLIP | ≥ 0.36 | 0,51 |

#### SR CERAMIC WITH GLYCERINE

|                        |        |      |
|------------------------|--------|------|
| FORWARD HEEL SLIP      | ≥ 0.19 | 0,36 |
| BACKWARD FOREPART SLIP | ≥ 0.22 | 0,35 |