

Chequer Plate Mat Single Bar - 3mm

Chequer Plate Matting is a low-cost surface covering, recommended for applications where safety and slip protection are crucial but without the need for anti-fatigue properties. The diamond-embossed chequer plate surface provides exceptional non-directional grip, making it suitable for workbenches as well as flooring.

This lightweight matting is available in both rolls and cut lengths.

Features

- ◆ **Typical applications:** Perfect for warehouse aisles, industrial walkways, as shelf liners, on workbenches and near machines to prevent objects sliding.
- ◆ **Material:** 100% rubber.
- ◆ **Cleaning:** Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended.
- ◆ **Sustainability:** Nature friendly, biodegradable and recyclable. REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- ◆ **Warranty:** Lifetime.



Suitable for indoor use




For more information about this product or, to place an order [click here](#)

Code	Metric	Imperial	Thickness	Weight	Type	Colour
CR3122-1	120cm x 10m	4' x 33'	3mm	35kg	Roll	Black
CR3122-1C	120cm wide	4' wide	3mm	3.5kg	Cut length - per m	Black

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

Chequer Plate Mat Single Bar - 3mm

Technical Specification

Slip resistant: Great slip resistance to level 2

Anti-fatigue: Good anti-fatigue properties, resistant to level 1

Wear resistant: Excellent wear resistance to level 3, suitable for heavy footfall

Cut to length: Yes, mat can be cut to length

Cut to size: Yes, mat can be cut to bespoke sizes

Disability friendly: Yes, the low profile makes it suitable for wheelchair users

Dry area: Yes

Wheeled area: Yes, the low profile allows easy access for wheeled traffic

Environment: Suitable for indoor use

Impact resistant: Yes

Product testing:

- ◆ Hardness: 85+/-5 shore A - DIN ISO 7619-1
- ◆ Volume weight: 1.82g/cm³ - DIN 53504
- ◆ Tensile strength: Direction 1 - 1690psi/direction 2 - 1940psi ASTM D412-16
- ◆ Elongation at break: 190% - ASTM D3574-17 Test E
- ◆ Puncture resistance - EN388:2016+A1:2028, Clause 6.5
- ◆ Indentation resistance - ASTM F970-17

Sustainability:

- ◆ Nature friendly, biodegradable and recyclable
- ◆ REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals)
- ◆ Contributes to a cleaner environment by reducing the need to use cleaning chemicals

Cleaning: Wash with cold water, use a vacuum cleaner, or a pressure pump to remove dirt. The use of harsh detergents is not recommended