



01905 794 875
StartSafety.uk

sales@startsafety.uk

# Forklift Mat

Forklift Mat provides optimal water absorption and effectively remove dirt brought into warehouses by forklift trucks. The polypropylene surface has been specially designed with an intricate weave to achieve maximum effectiveness in high traffic areas. Affixed using our double-sided adhesive tape, our Forklift Mat is suitable for the most demanding warehouse environments, reducing the risks of slips, trips, and falls.

The mat comes in a 90cm x 180cm tile and is designed to be able to cover large areas by laying them side by side. Adhesive tape sold separately.

#### Features

- Typical applications: Ideal for any environment where forklifts are operated, contributing to cleanliness, safety, and the protection of floor surfaces.
- Material: Polypropylene surface with rubber backing.
- Cleaning: Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt. The use of detergent is not recommended.
- Warranty: Lifetime. However, the longevity of the mat depends on how they are treated. We recommend that forklift operatives refrain from turning on the mats or placing/pushing pallets across them, as such actions can cause damage, resulting in early replacement.



Suitable for indoor use	<b>گ</b> _3	ുന് <mark>നം</mark> പ്പാം	෯	-,,,-	$\sim$	

For more information about this product, or to place an order **click here** For more information about our Double-Sided Adhesive Tape, **click here** 

Code	Metric	Imperial	Thickness	Weight	Colour
FM3672	90cm x 180cm	35" x 71"	8mm	9kgs	Charcoal

Please note, all Imperial sizes have either been rounded up or down to the nearest whole number



# **Forklift Mat**

<b>Technical Specification</b>			
Water absorbent:	Excellent water absorbency to level 3		
Soil resistant:	Excellent scraping and wiping function, resistant to level 3		
Disability friendly:	Yes, the low profile makes it suitable for wheelchair users		
Dry area:	Yes		
Wet area:	Yes		
Heavy area:	Yes		
Environment:	Suitable for indoor use		
Forklifts:	Yes		
Product testing:	Rubber backing:     ◆   Hardness: 55+ shore A     ◆   DIN abrasion loss mm <sup>3</sup> : 250-300     ◆   Tensile strength: 3-3.5Mpa		
Temperature resistance:	-20°C to 110° C		



# Forklift Mat

#### **Double-Sided Adhesive Tape Application**

#### 1 roll of tape = 4 mats

