

TECHNICAL SPECIFICATION



Steel Twist Lock Karabiner

Steel Twist Lock Karabiner / FAR0903



DESCRIPTION

Steel self-closing & automatic locking connector.

OPTIONS

Steel Twist Lock Karabiner (FAR0903)

SAFETY STANDARDS

EN 362



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 8 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Material
Galvanised Steel

Gate Opening
22mm

Product Weight
236g

Connector Type
Self Closing And Automatic Locking



Rated Weight / Load
40kN Breaking Load



DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0902-far0903.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 8 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

