





Rubber Rib Mat

Rubber Rib Mat is a low cost, surface covering suitable for use in a wide variety of applications. The ribbed surface provides excellent grip for both floor surfaces and work areas alike. It is easy to cut and can be laid loose or glued/fixed down for a more permanent solution. Available in two different thicknesses, 3mm and 6mm, Rubber Rib Mat is suitable for medium to heavy duty use.

Features

- Typical applications: Low-cost surface covering, suitable for industrial flooring, aisles, work benches, vehicle interiors, kennels, livery enclosures and animal grooming areas.
- Material: 100% rubber.
- Cleaning: Wash with cold water, use vacuum cleaner, or use pressure pump to remove dirt. The use of hard detergents is not recommended.
- Sustainability: REACH compliant. Contributes to a cleaner environment by reducing the need to use cleaning chemicals.
- Warranty: Lifetime.

























For more information about this product or, to place an order click here

| Code | Metric | Imperial | Thickness | Weight | Туре | Colour |
|---------|-------------|----------|-----------|--------|--------------------|--------|
| RR391 | 90cm x 10m | 3' x 33' | 3mm | 26.1kg | Roll | Black |
| RR691 | 90cm x 10m | 3' x 33' | 6mm | 76kg | Roll | Black |
| RR6100 | 100cm x 10m | 3' x 33' | 6mm | 83kg | Roll | Black |
| RR3122 | 120cm x 10m | 4' x 33' | 3mm | 35kg | Roll | Black |
| RR6122 | 120cm x 10m | 4' x 33' | 6mm | 97kg | Roll | Black |
| RR391C | 90cm wide | 3' wide | 3mm | 3kg | Cut length - per m | Black |
| RR691C | 90cm wide | 3' wide | 6mm | 7.6kg | Cut length - per m | Black |
| RR6100C | 100cm wide | 3' wide | 6mm | 8.3kg | Cut length - per m | Black |



Rubber Rib Mat

| Code | Metric | Imperial | Thickness | Weight | Туре | Colour |
|---------|------------|----------|-----------|--------|--------------------|--------|
| RR3122C | 120cm wide | 4' wide | 3mm | 3.5kg | Cut length - per m | Black |
| RR6122C | 120cm wide | 4' wide | 6mm | 9.7kg | Cut length - per m | Black |

Please note, the width and length can be +/- 2% Please note, all Imperial sizes have either been rounded up or down to the nearest whole number

| Technical Specification | | | |
|--------------------------------|--|--|--|
| Slip resistant: | Great slip resistance to level 2 | | |
| Anti-fatigue: | Good anti-fatigue properties, resistant to level 1 | | |
| Wear resistant: | Great wear resistance to level 2, suitable for medium to high footfall | | |
| Cut to length: | Yes, mat can be cut to length | | |
| Cut to size: | Yes, mat can be cut to bespoke sizes | | |
| Disability friendly: | Yes, the low profile makes it suitable for wheelchair users | | |
| Dry area: | Yes | | |
| Wheeled area: | Yes, the low profile allows easy access for light weight wheeled traffic | | |
| Environment: | Suitable for indoor and outdoor use | | |
| Impact resistant: | Yes | | |
| Product testing: | → Hardness Shore A ±5 65° ISO 7619-1 → SG (g/cm²) 1.50 ISO 2781 → Tensile (N/mm²) 2.5 ISO 37 → Elongation % 200 ISO 37 | | |
| Sustainability: | REACH (Registration, Evaluation, Authorisation and Restrictions of Chemicals) Contributes to a cleaner environment by reducing the need to use cleaning chemicals | | |
| Cleaning: | Wash with cold water, use vacuum cleaner, or use pressure pump to remove dirt. The use of hard detergents is not recommended | | |