

TuffTrak XT

Temporary Roadway | Working Pads | Turf & Ground Protection

TuffTrak

®



TuffTrak® XT the 'extreme' heavy duty road mat



- » Overall 13'5" (4000mm) x 6'8" (2000mm) x 3.54" (90mm)
- » Cellular core High Molecular Weight (HMW) Polyethylene construction delivering:
 - 'Buoyancy' capability
 - Unique chevron traction® surface nub design for maximum grip
 - 'Hybrid' overlaps for extra strength at connector and corner points
 - 16 fixing points
 - Unique Four3 cam lock connector / fixing pin (Patent Pending)
 - Unique location of connector points for corner / fan deployment
 - Reversible surface
 - 73.625ft² (6.84m²) usable surface area
- » 30,722 lbs / ft² (150 tonnes / m²)
- » 50 mats loaded per 40ft container / truck



Heavy duty 'buoyant' temporary access for all weather and ground conditions especially wetlands, marshlands, peat bogs, and river deltas;

- » Pipelines
- » Transmission
- » Civil Engineering
- » Infrastructure
- » Construction
- » Military Sites
- » Oil & Gas

Unique Four3 Connector



- » Simple and robust
- » Quarter turn locking
- » Unique location of connector fixing points
- provides adjustment and corner / fan deployment
- » Tool extraction positions
- » One piece moulded polymer for strength and durability
- » Stainless steel core

Technical Specifications



Material:	Prime HMWPE (UHMWPE optional)	
Dimensions:		
Length:	13'5"	4000mm
Width:	6'8"	2000mm
Depth:	3.54"	90mm
Weight:	770 lbs	350kg
Surface Area:	73.625ft ²	6.84m ²
Transportation:	50 x TuffTrak XT per 40ft container / Truck	