



U GROUP SRL
Via Borgomanero n° 1
28040 Paruzzaro (NO)

LEGAL DATA:
C.F e Reg.Imp.Novara:02041920030
CCIAA Novara REA: 211799
P.IVA: IT02041920030
Codice Export: No015724
Cap.Soc.: 119.000 lv

CONTACTS:
WEBSITE: www.u-power.it/it
EMAIL: info@u-power.it
TEL: +39 0322 53 94 01
FAX: +39 0322 23 00 01

REV. 27/05/2024

DATA SHEET

PRODUCT PICTURE

RANGES

TECHNOLOGIES

RR20016 COAL S1P SRC
Natural Confort 11 Mondopoint
AirToe Composite
SHOE TYPE "A"
SIZE RANGE 35-48 (UK: 2-13)
Size tested: 42 - WEIGHT Kg 1,065



ROCK&ROLL



DESCRIPTION

TECHNICAL SPECIFICATIONS

EN ISO STANDARD

VALUE

Safety shoes low totally "metal free", U-Power comfortable and light of the "Rock & Roll" range, with Airmet upper in soft perforated suede leather, inserts in breathable mesh, tip AirToe Composite, antiperforation, anti-slip and PU / PU sole, S1P SRC

SAFETY TOE CAP "AirToe Composite"

Impact resistance. Free heights after collision mm
Compressive strength. Free heights after compr. mm

20345:2011
RESULT
≥ 14 19,0
≥ 14 19,0

INSOLE "Save & Flex PLUS"

Puncture resistance N

≥ 1100 Compliant

ELECTRICAL RESISTANCE CATEGORY

Environmental class 1 - 12% humidity
Environmental class 2 - 25% humidity
Environmental class 3 - 50% humidity

10⁵ Ω e 10⁹ Ω (0,1 MΩ a 100 MΩ) < 10⁹ Ohm
10⁵ Ω e 10⁹ Ω (0,1 MΩ a 100 MΩ) < 10⁹ Ohm
10⁵ Ω e 10⁹ Ω (0,1 MΩ a 100 MΩ) < 10⁹ Ohm

UPPER DYNAMIC WATERPROOFING AFTER 60'

Water absorption after 60'
Water transmitted after 60'
Permeability to water vapor mg/(cm² h)
Permeability coefficient mg/cm²

≤ 30% N.A.
≤ 0.2 gr N.A.
≥ 0.8 10,6
≥ 15 92,7

VAMP LINING

Permeability to water vapor mg/(cm² h)
Permeability coefficient mg/cm²
Resistance to abrasion - DRY cycles
Resistance to abrasion - WET cycles

≥ 2 63,3
≥ 20 506,8
25600 cycles No hole
12800 cycles No hole

INSOLE

Abrasion resistance

≥ 400 cycles No damage

SOLE WEAR

Abrasion resistance (volume loss) mm³
Bending resistance mm
Resistance to sole / midsole detachment N/mm
Hydrocarbons resistance (% volume variation)
Heel energy absorption J
Adherence coef. with EN 13207 SRB method
Adherence coef. with EN 13207 SRA method

≤ 150 95
≤ 4 3,2
≥ 3 4,1
≤ 12 2,9
≥ 20 20
≥ 0.18 0,44
≥ 0.32 0,45