



U GROUP SRL
Via Borgomanero n° 1
28040 Paruzzaro (NO)

LEGAL DATA:
C.F e Reg.Imp.Novara:02041920030
CCIAA Novara REA: 211799
P.IVA: IT02041920030
Codice Export: No015724
Cap.Soc.: 119.000 lv

CONTACTS:
WEBSITE: www.u-power.it/it
EMAIL: info@u-power.it
TEL: +39 0322 53 94 01
FAX: +39 0322 23 00 01

REV. 27/05/2024

DATA SHEET

PRODUCT PICTURE

RANGES

TECHNOLOGIES

SN20014 KING S3 SRC
Natural Confort 11 Mondopoint
AirToe Aluminium
SHOE TYPE "A"
SIZE RANGE 35-48 (UK: 2-13)
Size tested: 42 - WEIGHT Kg 1,107



THE ROAR...



DESCRIPTION

TECHNICAL SPECIFICATIONS

EN ISO STANDARD

VALUE

Safety shoes low, light and comfortable U-Power of the The Roar range, with tumbled natural Nubuck leather upper, water-repellent, aluminum toecap, anti-puncture, anti-slip and PU / PU LIGHT GRIP sole, S3 SRC

SAFETY TOE CAP "AirToe Aluminium"

Impact resistance. Free heights after collision mm
Compressive strength. Free heights after compr. mm

20345:2011
RESULT
≥ 14 20,0
≥ 14 20,5

INSOLE "Save & Flex PLUS® , pierce resistant "non metal" "

Puncture resistance N

≥ 1100 Compliant

ELECTRICAL RESISTANCE CATEGORY

Environmental class 1 - 12% humidity
Environmental class 2 - 25% humidity
Environmental class 3 - 50% humidity

10⁵ Ω e 10⁹ Ω (0,1 MΩ a 100 MΩ) < 10⁹ Ohm
10⁵ Ω e 10⁹ Ω (0,1 MΩ a 100 MΩ) < 10⁹ Ohm
10⁵ Ω e 10⁹ Ω (0,1 MΩ a 100 MΩ) < 10⁹ Ohm

UPPER DYNAMIC WATERPROOFING AFTER 60'

Water absorption after 60'
Water transmitted after 60'
Permeability to water vapor mg/(cm² h)
Permeability coefficient mg/cm²

≤ 30% 14
≤ 0.2 gr 0,1
≥ 0.8 7,2
≥ 15 64,4

VAMP LINING

Permeability to water vapor mg/(cm² h)
Permeability coefficient mg/cm²
Resistance to abrasion - DRY cycles
Resistance to abrasion - WET cycles

≥ 2 4,7
≥ 20 42,5
25600 cycles No hole
12800 cycles No hole

INSOLE

Abrasion resistance

≥ 400 cycles No damage

SOLE WEAR

Abrasion resistance (volume loss) mm³
Bending resistance mm
Resistance to sole / midsole detachment N/mm
Hydrocarbons resistance (% volume variation)
Heel energy absorption J
Adherence coef. with EN 13207 SRB method
Adherence coef. with EN 13207 SRA method

≤ 150 69
≤ 4 1,5
≥ 3 4,5
≤ 12 6
≥ 20 30
≥ 0.18 0,19
≥ 0.32 0,48