



**U GROUP SRL**  
Via Borgomanero n° 1  
28040 Paruzzaro (NO)

**LEGAL DATA:**  
C.F e Reg.Imp.Novara:02041920030  
CCIAA Novara REA: 211799  
P.IVA: IT02041920030  
Codice Export: No015724  
Cap.Soc.: 119.000 lv

**CONTACTS:**  
WEBSITE: www.u-power.it/it  
EMAIL: info@u-power.it  
TEL: +39 0322 53 94 01  
FAX: +39 0322 23 00 01

**REV. 27/05/2024**

**DATA SHEET**

**PRODUCT PICTURE**

**RANGES**

**TECHNOLOGIES**

SN10014 LION S3 SRC  
Natural Confort 11 Mondopoint  
AirToe Aluminium  
SHOE TYPE "B"  
SIZE RANGE 35-48  
Size tested: 42 - WEIGHT Kg 1,116



**THE ROAR...**



**DESCRIPTION**

**TECHNICAL SPECIFICATIONS**

**EN ISO STANDARD**

**VALUE**

Safety shoes high, light and comfortable U-Power of the The Roar range, with tumbled natural Nubuck leather upper, water-repellent, aluminum toecap, anti-puncture, anti-slip and PU / PU LIGHT GRIP sole, S3 SRC

**SAFETY TOE CAP "AirToe Aluminium"**

Impact resistance. Free heights after collision mm  
Compressive strength. Free heights after compr. mm

**20345:2011**  
**RESULT**  
≥ 14 20,0  
≥ 14 20,5

**INSOLE "Save & Flex PLUS® , pierce resistant "non metal" "**

Puncture resistance N

≥ 1100 Compliant

**ELECTRICAL RESISTANCE CATEGORY**

Environmental class 1 - 12% humidity  
Environmental class 2 - 25% humidity  
Environmental class 3 - 50% humidity

10<sup>5</sup> Ω e 10<sup>9</sup> Ω (0,1 MΩ a 100 MΩ) < 10<sup>9</sup> Ohm  
10<sup>5</sup> Ω e 10<sup>9</sup> Ω (0,1 MΩ a 100 MΩ) < 10<sup>9</sup> Ohm  
10<sup>5</sup> Ω e 10<sup>9</sup> Ω (0,1 MΩ a 100 MΩ) < 10<sup>9</sup> Ohm

**UPPER DYNAMIC WATERPROOFING AFTER 60'**

Water absorption after 60'  
Water transmitted after 60'  
Permeability to water vapor mg/(cm<sup>2</sup> h)  
Permeability coefficient mg/cm<sup>2</sup>

≤ 30% 4,5  
≤ 0.2 gr 0,0  
≥ 0.8 6,9  
≥ 15 70,5

**VAMP LINING**

Permeability to water vapor mg/(cm<sup>2</sup> h)  
Permeability coefficient mg/cm<sup>2</sup>  
Resistance to abrasion - DRY cycles  
Resistance to abrasion - WET cycles

≥ 2 24,7  
≥ 20 197,9  
25600 cycles No hole  
12800 cycles No hole

**INSOLE**

Abrasion resistance

≥ 400 cycles No damage

**SOLE WEAR**

Abrasion resistance (volume loss) mm<sup>3</sup>  
Bending resistance mm  
Resistance to sole / midsole detachment N/mm  
Hydrocarbons resistance (% volume variation)  
Heel energy absorption J  
Adherence coef. with EN 13207 SRB method  
Adherence coef. with EN 13207 SRA method

≤ 150 69  
≤ 4 1,5  
≥ 3 4,6  
≤ 12 6  
≥ 20 30  
≥ 0.18 0,19  
≥ 0.32 0,48