



**U GROUP SRL**  
Via Borgomanero n° 1  
28040 Paruzzaro (NO)

**LEGAL DATA:**  
C.F e Reg.Imp.Novara:02041920030  
CCIAA Novara REA: 211799  
P.IVA: IT02041920030  
Codice Export: No015724  
Cap.Soc.: 119.000 lv

**CONTACTS:**  
WEBSITE: www.u-power.it/it  
EMAIL: info@u-power.it  
TEL: +39 0322 53 94 01  
FAX: +39 0322 23 00 01

**REV. 27/05/2024**

**DATA SHEET**

**PRODUCT PICTURE**

**RANGES**

**TECHNOLOGIES**

RL20484 MORGAN S3 SRC CI ESD  
Natural Confort 11 Mondopoint  
AirToe Composite  
SHOE TYPE "A"  
SIZE RANGE 35-48 (UK: 5-13)  
Size tested: 42 - WEIGHT Kg 1,2441



**WHITE68&BLACK**



**DESCRIPTION**

**TECHNICAL SPECIFICATIONS**

**EN ISO STANDARD**

**VALUE**



Safety shoes low, light and comfortable U-Power of the Red Lion range, totally "metal free", with New safety dry upper, composite toecap, water-repellent, anti-puncture, anti-slip and PU / PU infenergy, S3 CI SRC ESD sole

**SAFETY TOE CAP "AirToe Composite"**

Impact resistance. Free heights after collision mm  
Compressive strength. Free heights after compr. mm

**INSOLE "Save & Flex PLUS® , pierce resistant "non metal" "**

Puncture resistance N

**ELECTRICAL RESISTANCE CATEGORY**

Environmental class 1 - 12% humidity  
Environmental class 2 - 25% humidity  
Environmental class 3 - 50% humidity

**UPPER DYNAMIC WATERPROOFING AFTER 60'**

Water absorption after 60'  
Water transmitted after 60'  
Permeability to water vapor mg/(cm<sup>2</sup> h)  
Permeability coefficient mg/cm<sup>2</sup>

**VAMP LINING**

Permeability to water vapor mg/(cm<sup>2</sup> h)  
Permeability coefficient mg/cm<sup>2</sup>  
Resistance to abrasion - DRY cycles  
Resistance to abrasion - WET cycles

**INSOLE**

Abrasion resistance

**SOLE WEAR**

Abrasion resistance (volume loss) mm<sup>3</sup>  
Bending resistance mm  
Resistance to sole / midsole detachment N/mm  
Hydrocarbons resistance (% volume variation)  
Heel energy absorption J  
Adherence coef. with EN 13207 SRB method  
Adherence coef. with EN 13207 SRA method

EN ISO STANDARD	VALUE
<b>20345:2011</b>	<b>RESULT</b>
≥ 14	17,0
≥ 14	17,0
≥ 1100	Compliant
10 <sup>5</sup> Ω e 10 <sup>9</sup> Ω (0,1 MΩ a 100 MΩ)	< 10 <sup>8</sup> Ohm
10 <sup>5</sup> Ω e 10 <sup>9</sup> Ω (0,1 MΩ a 100 MΩ)	< 10 <sup>8</sup> Ohm
10 <sup>5</sup> Ω e 10 <sup>9</sup> Ω (0,1 MΩ a 100 MΩ)	< 10 <sup>8</sup> Ohm
≤ 30%	12
≤ 0.2 gr	0,0
≥ 0.8	1,8
≥ 15	16,7
≥ 2	10,4
≥ 20	86,7
25600 cycles	No hole
12800 cycles	No hole
≥ 400 cycles	No damage
≤ 150	55
≤ 4	1,0
≥ 3	5,0
≤ 12	1
≥ 20	34
≥ 0.18	0,24
≥ 0.32	0,68