



U GROUP SRL
Via Borgomanero n° 1
28040 Paruzzaro (NO)

LEGAL DATA:
C.F e Reg.Imp.Novara:02041920030
CCIAA Novara REA: 211799
P.IVA: IT02041920030
Codice Export: No015724
Cap.Soc.: 119.000 Iv

CONTACTS:
WEBSITE: www.u-power.it/it
EMAIL: info@u-power.it
TEL: +39 0322 53 94 01
FAX: +39 0322 23 00 01

REV. 27/05/2024

DATA SHEET

PRODUCT PICTURE

RANGES

TECHNOLOGIES

RV20044 PETER S3 SRC CI ESD
Natural Confort 11 Mondopoint
AirToe Aluminium
SHOE TYPE "A"
SIZE RANGE 35-48
Size tested: 42 - WEIGHT Kg 1,1251



DESCRIPTION

TECHNICAL SPECIFICATIONS

EN ISO STANDARD

VALUE

Low-heeled S3 SRC CI ESD protection class **safety shoes** with **PU TEK® star** upper and toe protection with abrasion-resistant scuff cap.

Ultra-light work shoes highly resistant to abrasion and with particular **protection of the sole from the cold**. These **non-slip shoes** with **anti-static, oil-resistant** and **abrasion-resistant soles** are fitted with a **tread** made with a particular super-light **new generation** PU compound that considerably reduces the overall weight of the shoe.

The **AirToe Aluminium toecap** and the **new ultra-light puncture-resistant textile insole**, ensure protection of toe and sole of the foot while preserving the lightness of the shoe.

Well-being and comfort are ensured by the presence of the breathable **U-Power Original insole** in light polyurethane compound, while breathability is increased by the **Wingtex air tunnel lining** which guarantees air circulation and moisture absorption.

Safety footwear suitable for: **craftsmen** in general, **electricians, carpenters, warehouse workers**, and the **transport and logistics sector**.

SAFETY TOE CAP "AirToe Aluminium"

Impact resistance. Free heights after collision mm
Compressive strength. Free heights after compr. mm

INSOLE "Save & Flex Air"

Puncture resistance N

ELECTRICAL RESISTANCE CATEGORY

Environmental class 1 - 12% humidity

Environmental class 2 - 25% humidity

Environmental class 3 - 50% humidity

UPPER DYNAMIC WATERPROOFING AFTER 60'

Water absorption after 60'

Water transmitted after 60'

Permeability to water vapor mg/(cm² h)

Permeability coefficient mg/cm²

VAMP LINING

Permeability to water vapor mg/(cm² h)

Permeability coefficient mg/cm²

Resistance to abrasion - DRY cycles

Resistance to abrasion - WET cycles

INSOLE

Abrasion resistance

SOLE WEAR

Abrasion resistance (volume loss) mm³

Bending resistance mm

Resistance to sole / midsole detachment N/mm

Hydrocarbons resistance (% volume variation)

Heel energy absorption J

Adherence coef. with EN 13207 SRB method

Adherence coef. with EN 13207 SRA method

	20345:2011	RESULT
≥ 14		19,0
≥ 14		19,5
≥ 1100		Compliant
10 ⁵ Ω e 10 ⁹ Ω (0,1 MΩ a 100 MΩ)		< 10 ⁸ Ohm
10 ⁵ Ω e 10 ⁹ Ω (0,1 MΩ a 100 MΩ)		< 10 ⁸ Ohm
10 ⁵ Ω e 10 ⁹ Ω (0,1 MΩ a 100 MΩ)		< 10 ⁸ Ohm
≤ 30%		8.0
≤ 0.2 gr		0
≥ 0.8		10.2
≥ 15		82.9
≥ 2		96.3
≥ 20		770.5
25600 cycles		No hole
12800 cycles		No hole
≥ 400 cycles		No damage
≤ 150		37
≤ 4		0,8
≥ 3		N.A.
≤ 12		2,1
≥ 20		26
≥ 0.18		0,28
≥ 0.32		0,38