



U GROUP SRL
Via Borgomanero n° 1
28040 Paruzzaro (NO)

LEGAL DATA:
C.F e Reg.Imp.Novara:02041920030
CCIAA Novara REA: 211799
P.IVA: IT02041920030
Codice Export: No015724
Cap.Soc.: 119.000 lv

CONTACTS:
WEBSITE: www.u-power.it/it
EMAIL: info@u-power.it
TEL: +39 0322 53 94 01
FAX: +39 0322 23 00 01

REV. 27/05/2024

DATA SHEET

PRODUCT PICTURE

RANGES

TECHNOLOGIES

SO10043 PITUCON S3 SRC
Natural Confort 11 Mondopoint
AirToe Composite
SHOE TYPE "B"
SIZE RANGE 38-47 (UK: 5-12)
Size tested: 42 - WEIGHT Kg 1,329



STEP ONE



DESCRIPTION

TECHNICAL SPECIFICATIONS

EN ISO STANDARD

VALUE

Ankle boots safety shoes, U-Power, comfortable and breathable of the Step One range, with soft water-repellent grained leather upper, composite toe cap, anti-puncture, anti-slip, ergonomic steel foil and PU/PU sole, S3 SRC

SAFETY TOE CAP "AirToe Composite"

Impact resistance. Free heights after collision mm ≥ 14
Compressive strength. Free heights after compr. mm ≥ 14

INSOLE "Classic steel midsole"

Puncture resistance N ≥ 1100

ELECTRICAL RESISTANCE CATEGORY

Environmental class 1 - 12% humidity $10^5 \Omega$ e $10^9 \Omega$ (0,1 M Ω a 100 M Ω) $< 10^9$ Ohm
Environmental class 2 - 25% humidity $10^5 \Omega$ e $10^9 \Omega$ (0,1 M Ω a 100 M Ω) $< 10^9$ Ohm
Environmental class 3 - 50% humidity $10^5 \Omega$ e $10^9 \Omega$ (0,1 M Ω a 100 M Ω) $< 10^9$ Ohm

UPPER DYNAMIC WATERPROOFING AFTER 60'

Water absorption after 60' $\leq 30\%$ 14
Water transmitted after 60' ≤ 0.2 gr 0,1
Permeability to water vapor mg/(cm² h) ≥ 0.8 3,2
Permeability coefficient mg/cm² ≥ 15 27,1

VAMP LINING

Permeability to water vapor mg/(cm² h) ≥ 2 4,7
Permeability coefficient mg/cm² ≥ 20 42,5
Resistance to abrasion - DRY cycles 25600 cycles No hole
Resistance to abrasion - WET cycles 12800 cycles No hole

INSOLE

Abrasion resistance ≥ 400 cycles No damage

SOLE WEAR

Abrasion resistance (volume loss) mm³ ≤ 150 56
Bending resistance mm ≤ 4 2,3
Resistance to sole / midsole detachment N/mm ≥ 3 4,1
Hydrocarbons resistance (% volume variation) ≤ 12 3
Heel energy absorption J ≥ 20 40
Adherence coef. with EN 13207 SRB method ≥ 0.18 0,20
Adherence coef. with EN 13207 SRA method ≥ 0.32 0,38

20345:2011

RESULT