



**U GROUP SRL**  
Via Borgomanero n° 1  
28040 Paruzzaro (NO)

**LEGAL DATA:**  
C.F e Reg.Imp.Novara:02041920030  
CCIAA Novara REA: 211799  
P.IVA: IT02041920030  
Codice Export: No015724  
Cap.Soc.: 119.000 lv

**CONTACTS:**  
WEBSITE: www.u-power.it/it  
EMAIL: info@u-power.it  
TEL: +39 0322 53 94 01  
FAX: +39 0322 23 00 01

**REV. 27/05/2024**

**DATA SHEET**

**PRODUCT PICTURE**

**RANGES**

**TECHNOLOGIES**

RI11334 THANOS S3 SRC CI ESD  
Natural Confort 11 Mondopoint®  
AirToe Composite  
SHOE TYPE "B"  
SIZE RANGE 38-48  
Size tested: 42 - WEIGHT Kg 1,49



**BAU & BUILDING**



**DESCRIPTION**

**TECHNICAL SPECIFICATIONS**

**EN ISO STANDARD**

**VALUE**

Anti-static, water repellent shoes in soft, extremely robust, Pull-up leather, resistant to abrasion and dynamic traction. PU-reinforced scuff cap on the front and with double yellow and black lace.

These safety shoes, particularly suitable for use outdoors, have a AirToe Composite toe cap and Save & Flex® PLUS, all-fabric, anti-puncture system which guarantees protection and safety.

Protection class S3 CI SRC ESD, with special insulation on the bottom of the shoe against cold and an anti-slip, anti-static, abrasion resistant and oil resistant sole.

The WingTex air tunnel inner lining makes these safety shoes particularly breathable, whilst the anti-bacterial, anatomical, ultra-breathable insole ensures prolonged comfort.

These safety work shoes are perfect for use in outdoor environments, on uneven ground and treacherous surfaces, in wet and cold environments such as installations, construction and building sites, port areas, road works and maintenance, agriculture and gardens.

**SAFETY TOE CAP "AirToe Composite"**

Impact resistance. Free heights after collision mm  
Compressive strength. Free heights after compr. mm

**INSOLE "Save & Flex PLUS®, anti-puncture, "no metal" fabric insole"**

Puncture resistance N

**ELECTRICAL RESISTANCE CATEGORY**

Environmental class 1 - 12% humidity  
Environmental class 2 - 25% humidity  
Environmental class 3 - 50% humidity

**UPPER DYNAMIC WATERPROOFING AFTER 60'**

Water absorption after 60'  
Water transmitted after 60'

Permeability to water vapor mg/(cm<sup>2</sup> h)  
Permeability coefficient mg/cm<sup>2</sup>

**VAMP LINING**

Permeability to water vapor mg/(cm<sup>2</sup> h)  
Permeability coefficient mg/cm<sup>2</sup>

Resistance to abrasion - DRY cycles  
Resistance to abrasion - WET cycles

**INSOLE**

Abrasion resistance

**SOLE WEAR**

Abrasion resistance (volume loss) mm<sup>3</sup>  
Bending resistance mm  
Resistance to sole / midsole detachment N/mm  
Hydrocarbons resistance (% volume variation)  
Heel energy absorption J  
Adherence coef. with EN 13207 SRB method  
Adherence coef. with EN 13207 SRA method

**20345:2011**

**RESULT**

≥ 14	17,0
≥ 14	17,0
≥ 1100	Compliant
10 <sup>5</sup> Ω e 10 <sup>9</sup> Ω (0,1 MΩ a 100 MΩ)	< 10 <sup>8</sup> Ohm
10 <sup>5</sup> Ω e 10 <sup>9</sup> Ω (0,1 MΩ a 100 MΩ)	< 10 <sup>8</sup> Ohm
10 <sup>5</sup> Ω e 10 <sup>9</sup> Ω (0,1 MΩ a 100 MΩ)	< 10 <sup>8</sup> Ohm
≤ 30%	0
≤ 0.2 gr	6.4
≥ 0.8	2,9
≥ 15	29,7
≥ 2	55,7
≥ 20	445,8
25600 cycles	No hole
12800 cycles	No hole
≥ 400 cycles	No damage
≤ 150	-
≤ 4	0
≥ 3	4,2
≤ 12	1.5
≥ 20	36
≥ 0.18	0,28
≥ 0.32	0,43