

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: 001371 Issue date: 05/06/2025 Version: 1.0

issue date. 05/00/2025 Version. 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Trade name : ULTRACRETE PAK SPRAY
UFI : A001-K0TS-D00Y-6CS7
Product code : ULTRACRETE PAK SPRAY

Product group : Finished product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

1.2.2. Uses advised against
No additional information available

### 1.3. Details of the supplier of the safety data sheet

Instarmac PLC

Unit W3A

Danny Morson Way

Birch Coppice Business Park

B78 1SE Dordon Tamworth, Warwickshire

England

T +44 (0)1827 254400

email@instarmac.co.uk, www.instarmac.co.uk

### 1.4. Emergency telephone number

No additional information available

### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Aerosol, Category 3 H229
Flammable liquids, Category 1 H224
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02 GHS07

Signal word (CLP) : Danger

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains : acetone; propan-2-one; propanone; ALIPHATIC HYDROCARBON (D40); n-butyl acetate;

ethyl acetate

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H224 - Extremely flammable liquid and vapour. H229 - Pressurised container: May burst if heated. H336 - May cause drowsiness or dizziness.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P251 - Do not pierce or burn, even after use.

EUH-statements : EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

#### 2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

### Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).]	CAS-No.: 68476-85-7 EC-No.: 270-704-2 EC Index-No.: 649-202-00-6	≥ 40	Press. Gas Flam. Gas 1, H220 Carc. 1A, H350 Muta. 1B, H340
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	CAS-No.: 64742-95-6 EC-No.: 265-199-0 EC Index-No.: 649-356-00-4	≥ 5 - < 20	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304
acetone; propan-2-one; propanone	CAS-No.: 67-64-1 EC-No.: 200-662-2 EC Index-No.: 606-001-00-8	≥1-<5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
ALIPHATIC HYDROCARBON (D40)	EC-No.: 919-857-5	≥1-<5	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	≥ 1 – < 5	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
ethyl acetate	CAS-No.: 141-78-6 EC-No.: 205-500-4 EC Index-No.: 607-022-00-5	≥ 1 – < 5	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 μm]	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-00-2	< 5	Carc. 2, H351

Full text of H- and EUH-statements: see section 16

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with

water for several minutes. If eye irritation persists: Get immediate medical advice/attention.

First-aid measures after ingestion : Not expected to present a significant hazard under anticipated conditions of normal use.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing).

Symptoms/effects after skin contact : None under normal conditions. Contact with the liquefied gas may cause frostbite. May

cause moderate irritation.

Symptoms/effects after eye contact : May cause eye irritation.

Symptoms/effects after ingestion : May cause irritation to the digestive tract.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.

Explosion hazard : Pressurised container: May burst if heated. May form flammable/explosive vapour-air

mixture. Vapours are heavier than air and may travel considerable distance to an ignition

source and flash back to source of vapours.

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Precautionary measures fire : Eliminate all ignition sources if safe to do so. Evacuate area. Fight fire remotely due to the

risk of explosion. Cool down the containers exposed to heat with a water spray.

05/06/2025 (Issue date) EN (English) 3/15

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper

protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters.

Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment. Ensure adequate ventilation.

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing

dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Remove all sources of ignition. Absorb spilled material with sand or earth. Contain any spills

with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak

without risks if possible.

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Storage class (LGK, TRGS 510)

Joint storage table

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

Precautions for safe handling : Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing

dust/fume/gas/mist/vapours/spray. Ensure good ventilation of the work station.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product. Always wash nands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a

well-ventilated place. Keep cool.

Packaging materials : Store always product in container of same material as original container.

: LGK 2B - Aerosol dispensers and lighters

:	LGK 1	LGK 2A	LGK 2B	LGK 3	LGK 4.1A
	LGK 4.1B	LGK 4.2	LGK 4.3	LGK 5.1A	LGK 5.1B
	LGK 5.1C	LGK 5.2	LGK 6.1A	LGK 6.1B	LGK 6.1C
	LGK 6.1D	LGK 6.2	LGK 7	LGK 8A	LGK 8B
	LGK 10	LGK 11	LGK 12	LGK 13	LGK 10-13

05/06/2025 (Issue date) EN (English) 4/15

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Joint storage not permitted for : LGK 1, LGK 4.1A, LGK 4.1B, LGK 4.2, LGK 4.3, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.2,

LGK 7

Joint storage with restrictions permitted for : LGK 2A, LGK 5.1C

Joint storage permitted for : LGK 2B, LGK 3, LGK 6.1A, LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10,

LGK 11, LGK 12, LGK 13, LGK 10-13

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

No additional information available

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

### Personal protective equipment:

Wear recommended personal protective equipment.

#### Personal protective equipment symbol(s):







### 8.2.2.1. Eye and face protection

### Eye protection:

Safety glasses

Safety goggles	Droplet	Plastic	EN 166
Туре	Field of application	Characteristics	Standard
Eye protection			

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

### Hand protection:

Protective gloves

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection					
Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)				EN 374-2

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : white.

Appearance : Aerosol spray can.
Odour : Not available
Odour threshold : Not available
Melting point : Not applicable
Freezing point : Not available
Boiling point : Not available

Flammability : Extremely flammable aerosol.

Explosive properties : Pressurised container: May burst if heated.

Explosive limits : Not available
Lower explosion limit : Not available
Upper explosion limit : Not available

Flash point : < 40 °C data stated for propellant Auto-ignition temperature : 410 - 580 °C data stated for propellant

Decomposition temperature : Not available pH : Not available Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : 590 – 1760 hPa @45 degrees centigrade. Data stated for propellant

Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

#### 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Pressurised container: May burst if heated. Extremely flammable aerosol.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified Acute toxicity (dermal) Not classified Acute toxicity (inhalation) Not classified Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified Respiratory or skin sensitisation : Not classified : Not classified. Germ cell mutagenicity : Not classified. Carcinogenicity Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

acetone; propan-2	2-one; propanone (	(67-64-1)

STOT-single exposure May cause drowsiness or dizziness.

#### ALIPHATIC HYDROCARBON (D40)

STOT-single exposure May cause drowsiness or dizziness.

#### n-butyl acetate (123-86-4)

STOT-single exposure May cause drowsiness or dizziness.

#### ethyl acetate (141-78-6)

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified Aspiration hazard : Not classified

#### 11.2. Information on other hazards

No additional information available

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)

05/06/2025 (Issue date) EN (English) 7/15

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Not rapidly degradable

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

#### 12.5 Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Regional waste regulation

Waste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

Additional information

HP Code

- : Disposal must be done according to official regulations.
- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Disposal must be done according to official regulations.
- : Disposal must be done according to official regulations.
- : Do not re-use empty containers.
- : HP3 "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
  - HP5 "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

#### 14.1. UN number or ID number

 UN-No. (ADR)
 : UN 1950

 UN-No. (IMDG)
 : UN 1950

 UN-No. (IATA)
 : UN 1950

 UN-No. (ADN)
 : UN 1950

 UN-No. (RID)
 : UN 1950

05/06/2025 (Issue date) EN (English) 8/15

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Proper Shipping Name (ADR) : AEROSOLS Proper Shipping Name (IMDG) : AEROSOLS

Proper Shipping Name (IATA) : Aerosols, flammable

Proper Shipping Name (ADN) : AEROSOLS Proper Shipping Name (RID) : AEROSOLS

Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D) Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1 (40°C c.c.) Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1 Transport document description (ADN) : UN 1950 AEROSOLS, 2.1 Transport document description (RID) : UN 1950 AEROSOLS, 2.1

#### ADR

Transport hazard class(es) (ADR) : 2.1 Danger labels (ADR) : 2.1



#### **IMDG**

: 2.1 Transport hazard class(es) (IMDG) 2.1

Danger labels (IMDG)



#### IATA

Transport hazard class(es) (IATA) : 2.1 Danger labels (IATA) 2.1



#### ADN

Transport hazard class(es) (ADN) : 2.1 2.1

Danger labels (ADN)



Transport hazard class(es) (RID) : 2.1 Danger labels (RID) 2.1



### 14.4. Packing group

Packing group (ADR) : Not applicable Packing group (IMDG) : Not applicable

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

#### 14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

#### 14.6. Special precautions for user

### Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9

Transport category (ADR) : 2

Special provisions for carriage - Packages (ADR) : V14

Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

#### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277 Excepted quantities (IMDG) : E0 Packing instructions (IMDG) : P207, LP200 Special packing provisions (IMDG) : PP87, L2 EmS-No. (Fire) : F-D EmS-No. (Spillage) : S-U Stowage category (IMDG) : None Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

#### Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

### Inland waterway transport

Classification code (ADN) : 5F

Special provisions (ADN) : 190, 327, 344, 625

Limited quantities (ADN) : 1 L

Excepted quantities (ADN) : E0

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01, VE04

Number of blue cones/lights (ADN)

### Rail transport

Classification code (RID) : 5F

Special provisions (RID) : 190, 327, 344, 625

: 1

Limited quantities (RID) : 1L

05/06/2025 (Issue date) EN (English) 10/15

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Excepted quantities (RID) : E0

Packing instructions (RID) : P207, LP200 Special packing provisions (RID) : PP87, RR6, L2

Mixed packing provisions (RID) : MP9
Transport category (RID) : 2
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading : CW9, CW12

and handling (RID)

Colis express (express parcels) (RID) : CE2 Hazard identification number (RID) : 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

**REACH Annex XVII (Restriction List)** 

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

**REACH Annex XIV (Authorisation List)** 

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

**REACH Candidate List (SVHC)** 

Contains no substance(s) listed on the REACH Candidate List

**PIC Regulation (Prior Informed Consent)** 

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

**POP Regulation (Persistent Organic Pollutants)** 

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported within 24 hours.

Name	CAS-No.	Nomenclature	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Acetone	67-64-1	2914 11 00	ex 3824 99 92

Please see https://home-affairs.ec.europa.eu/policies/internal-security/counter-terrorism-and-radicalisation/protection/legislation-chemicals-used-home-made-explosives en

**Drug Precursors Regulation (273/2004)** 

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Acetone		67-64-1	2914 11 00	Category 3		Annex I

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

Austria

Ordinance on Flammable Liquids (VbF) Auto detect

**France** 

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

**Employment restrictions** : Observe restrictions according Act on the Protection of Working Mothers (MuSchG).

Observe restrictions according Act on the Protection of Young People in Employment

(JArbSchG).

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

Chemicals Prohibition Ordinance (ChemVerbotsV) : This product is subject to ChemVerbotsV Annex 2 Entry 2. The following requirement must

be observed: Basic requirements for the implementation of the submission (according to § 8

paragraph 1, 3 and 4).

Major Accidents Ordinance (12. BlmSchV) Is not subject to the Major Accidents Ordinance (12. BlmSchV)

Netherlands

: Z(1) - non biodegradable substances with hazardous properties for humans and the ABM category

environment (carcinogenicity/ mutagenicity/ reprotoxicity/bioacumulative potential/ toxicity or

persistence)

SZW-lijst van kankerverwekkende stoffen : Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons

produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately-40°C to 80°C (- 40°F to 176°F).], Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of

approximately 135°C to 210°C (275°F to 410°F).] are listed

Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons SZW-lijst van mutagene stoffen

> produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately-40°C to 80°C (- 40°F to 176°F).], Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of

approximately 135°C to 210°C (275°F to 410°F).] are listed

SZW-lijst van reprotoxische stoffen - Borstvoeding

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

: None of the components are listed

: None of the components are listed

: None of the components are listed

Denmark

Class for fire hazard : Class II-1 Store unit

Classification remarks R10 <H222;H224;H229;H336;H412>; Emergency management guidelines for the storage of

flammable liquids must be followed

**Danish National Regulations** : Young people below the age of 18 years are not allowed to use the product

The requirements from the Danish Working Environment Authorities regarding work with

carcinogens must be followed during use and disposal

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

05/06/2025 (Issue date) EN (English) 12/15

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Abbreviations and a	cronyms:
ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
РВТ	Persistent Bioaccumulative Toxic

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and ac	Abbreviations and acronyms:		
PNEC	Predicted No-Effect Concentration		
PPE	Personal protection equipment		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
TF	Technical function		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
TWA	Time Weighted Average		
VOC	Volatile Organic Compounds		
vPvB	Very Persistent and Very Bioaccumulative		
UFI	Unique Formula Identifier		

Full text of H- and EU	H-statements:
Aerosol 1	Aerosol, Category 1
Aerosol 3	Aerosol, Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 1	Flammable liquids, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H350	May cause cancer.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

The classification complies with : ATP 12

Instarmac SDS EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.